

Mathematical Validation Of Algorithmic Efficiency In Computational Data Science Applications

Dr. Mohammed Zabeeulla A N^{1*}, Dr. J. Gul Shaira Banu², Dr. Amit Prakash³, Mr. Ranveer Singh⁴, Madhulika⁵, Dr Atowar ul Islam⁶, Dr D C Upadhyay⁷

^{1*}Associate Professor, JAIN(Deemed-to-be University), Computer Science and IT, Email Id: zabee225@gmail.com

²Associate Professor, Department of Computer Science and Engineering, Er Perumal Manimekalai College of Engineering, Email Id: drgulshairabanu@gmail.com, Orcid Id:0000-0003-4877-8738

³Assistant Professor, University Department of Mathematics, Jai Prakash University, Chapra(Bihar), India, Email Id: a.amitprakash@gmail.com

⁴Technical head, Samta Research Alliance, Mathura, Uttar Pradesh, Email Id: rannu0188@gmail.com

⁵Assistant Professor, Department of Mathematics (School of Applied and Life Sciences), Uttarakhand University, Dehradun, Uttarakhand, Pin code- 248007, India, Email Id: madhulikachaudhary9@gmail.com

⁶Associate professor, Computer Science, University of Science and Technology Meghalaya, Ri-bhoi, 9th Mile, Meghalaya, Email ID: atowar91626@gmail.com, Orcid Id: 0000-0001-5345-0556

⁷Professor & Dean, Faculty of Basic and Applied Sciences, Department of Mathematics, Madhav University, Bharja, Abu Road, Rajasthan, Pin – 307026, Email Id: upadhyaydc@yahoo.com

Abstract

The role of algorithmic efficiency in computational data science is quite critical, as computational methods based on scalable and mathematically sound algorithms become more popular in modern applications. The paper provides a streamlined but mathematical justification of the effectiveness of widely known algorithms, such as searching, sorting, clustering, and simple optimization algorithms. The research does not use expensive computation software or empirical simulation but uses a theoretical approach based on step-counting, use of asymptotic notations and use of an example-based verification. The study shows the evident performance behaviour differences between the logarithmic complexity, linear complexity, linear-logarithmic complexity, and quadratic complexity classes through breaking down the algorithms into basic operation steps and examining their behaviour in terms of the size of the input. The results indicate that algorithms including Binary Search and Merge sort have very efficient growth behaviours whereas algorithms like Bubble sort and simple pair wise clustering have large growth changes in operations as their input increases. The above example-based validation also proves the correctness of the mathematical predictions indicating that there is a consistent correspondence between the theoretical growth patterns and the observed operational trends. In general, the findings indicate the need to understand the behaviour of algorithms based on transparent mathematics, which underscores the value of available analytical models that may be used to facilitate teaching and learning algorithms in computational data science as well as practices in algorithm selection. This method presents a background to subsequent research that aims to assess the performance of the algorithms without the use of the complicated computational experimentation.

Keywords: Algorithmic Efficiency, Computational Data Science, Complexity Analysis, Mathematical Validation, Performance Evaluation.

1. Introduction

The study of algorithmic efficiency has become an important focus in data science computational science in which the study of algorithmic growth has become a key determinant of performance and scalability. Asymptotic behaviour has become standard in describing algorithms using the Big-O notation which is an established mathematical expression by which algorithms are compared and how their long-term operational

characteristics are understood [1]. With the ongoing development of computational systems, the investigation of algorithmic properties and structural features has become an inalienable part of the current IT education, which allows students to become more acquainted with the foundational principles of designing algorithms and estimating their performance [2].

The importance of efficient algorithms is especially in applied fields, where the cost of computation can have a profound effect on the result. To illustrate, comparative research on the classification models reveals that the performance depends on the structuring of algorithms, as well as efficacy, thus cautionary research on the choice of predictive tools is essential [3]. There have also been improvements in search algorithms and the use of hybrid methods in the form of linear and binary search methods has yielded better results in operation behaviour under various data situations [4]. Likewise, the results of the comparison between sorting algorithms like the Quicksort and Merge sort have highlighted the superior attributes of the divide-and-conquer approach in enhancing processing speed and scalability [5].

In addition to classical algorithms research, the increasing access to real-life data has presented novel problems in computation, and efficient analytic techniques that can exchange reliability and accuracy in huge data processing have been addressed by researchers [6]. This efficiency requirement is also manifested in the growing demand of evolutionary computation and optimization methods to handle complex data science problems by better algorithmic design [7], [8]. In addition, there are also efficiency patterns that are identified through mathematical modelling in wider fields, e.g. educational systems, where hierarchical models identify high and low efficiency structures [9]. The field of algorithmic complexity is an ongoing research area with recent contributions that provide the exhaustive reviews of algorithms complexity estimation technique and new challenges and directions in analysis [10]. The developments also stretch to more sophisticated areas like neural networks where algorithmic efficiency is meticulously quantified to make training and inferences processes more efficient [11]. There is also the role of mathematical modelling in forecasting dynamic behaviours, such as the development of actual phenomena, where computational efficiency analysis is even broader applicable [12]. Example-based validation has also arisen as a useful method to test the correctness of the theoretical predictions, which is a simplified yet efficient method to test the behaviour of an algorithm [13]. The classical algorithms like Binary Search are still used as basic examples of efficient algorithms which give clear examples of logarithmic performance scaling [14].

Sorting algorithms are still a significant field of study, and it is continuing to work on improved and hybridized versions that can improve traditional methods like Merge Sort, Heap Sort, and Bubble Sort [15]. These studies can be added to the existing literature in discussing algorithmic efficiency because they demonstrate that better structural design can dramatically affect computational performance.

Combined, these views draw attention to the need of mathematically based methodology of analysing and proving algorithmic efficiency. The current work based on this premise utilizes the step counting and complexity notation along with an analysis based on simple examples to present a readily comprehensible mathematical validation of some widely used algorithms in computational data science.

2. Methodology

2.1 Research Approach

The research takes a basic theoretical method to learn and prove the efficacy of general algorithms applying straightforward mathematical thought. Rather than using

sophisticated computational tools or using artificial intelligence methods, the study emphasizes dissecting the algorithms into easily understandable steps and monitoring how the behaviour of the algorithm changes with varying input sizes. This is meant to apply basic mathematical principles to describe the efficiency of an algorithm, so that the process can be easily understood with no technical expertise.

2.2 Selection of Algorithms

There were few algorithms used and understood easily, and these were chosen to analyse. These involve simple searching and sorting algorithms, simple grouping or clustering processes and simple optimization processes. These algorithms were selected due to the fact that they are regularly addressed in the field of computational data science and can be justified with simple mathematical reasoning, which is appropriate in the study that focuses on the clarity and simplicity.

2.3 Mathematical Analysis of Algorithm Steps

All the chosen algorithms are analyzed by decomposing it into its separate steps and determining the number of operations needed to execute the task. The step-by-step decomposition gives the study the ability to estimate the amount of effort required by an algorithm on various input sizes. The number of operations increases is described using simple mathematical instruments, including sequences, elementary inequalities and arithmetic arguments. Such a method is useful in determining the number of steps that the algorithm takes to complete its work, whether it is small, moderate, or large.

2.4 Use of Complexity Notation

To express the efficiency of the algorithms, the study uses basic complexity notations, mainly Big-O and Big- Θ , in their simplest and most understandable forms. These notations are used to state the rate at which running time of an algorithm increases with an increase in the input size. There is application of only necessary concepts of complexity theory and explanations are made simple to understand so that the readers who are not in an advanced background in computational mathematics can follow the analysis.

2.5 Example-Based Verification

Small numerical cases are taken to make sure that the mathematical estimations replicate the behaviour of the algorithms that should be realised. These problems illustrate the performance of an algorithm with simple data, and that as the size of this input increases so does the amount of work done by the algorithm. The study validates the consistency of the efficiency estimates obtained by comparing the results of such examples with the mathematical predictions without the use of computational experiments and programming.

2.6 Comparison Framework

The results of the analysis of each algorithm separately are compared with each other in terms of their general growth trends and approximate time of execution. This comparison allows to determine which algorithms are more efficient and mathematically knowing why some of their performance is different. The comparison is also made in a clear and descriptive way allowing the readers to comprehend the conclusions without the necessity to have special knowledge of computer science.

2.7 Ensuring Clarity and Reproducibility

All the explanations are described in simple and understandable language to simplify the methodology to follow and repeat. The mathematical procedures are directly stated

without the use of advanced theories or programmes. As no elaborate calculations and coding habits are used, the reasoning process can be repeated by any person with the rudimentary knowledge of mathematics, and the transparency and credibility of the study is guaranteed.

3. Results

The study findings give the mathematical efficiency tunes of the chosen algorithms in the simple analytical structure as outlined in the methodology. Every algorithm was analyzed in terms of counting the steps, simple notation of complexity, and small number examples. The results underscore the changes in the performance of these algorithms with the input size and the efficiency of these algorithms in comparison with each other in a practical and comprehensible manner.

3.1 Mathematical Efficiency Patterns of Selected Algorithms

It was revealed that all the algorithms have a distinct and foreseeable pattern of growth as per the number of operations they run. Algorithms like the Linear Search proved to be very slow and showed a gradual yet steady rate of increment of operations which increased proportionately with the input. This confirmed that the algorithm operates in $O(n)$ time, as predicted using simple arithmetic step counting. In contrast, Binary Search showed a much slower growth rate, with the number of operations increasing only when the input doubled, matching the typical $O(\log n)$ behaviour. Such findings suggest that using the simple counting techniques, the efficiency of the simple algorithms can be statistically determined. In order to visualise the theoretical growth behaviour of the algorithms treated, the comparative growth curves are provided in Figure 1.




Figure 1. Growth Pattern Comparison of Algorithms Showing $O(\log n)$, $O(n)$, $O(n \log n)$, and $O(n^2)$ Behaviour

An overview of these algorithms and their corresponding theoretical complexity classifications is provided in Table 1.

Table 1. Complexity Classification of Selected Algorithms

Algorithm Type	Algorithm Name	Mathematical Growth Pattern	Complexity Notation	Efficiency Level
Searching	Linear Search	Increases directly with n	$O(n)$	Moderate
Searching	Binary Search	Increases very slowly	$O(\log n)$	High
Sorting	Bubble Sort	Grows rapidly with n^2	$O(n^2)$	Low
Sorting	Merge Sort	Moderate, balanced growth	$O(n \log n)$	High
Grouping/Clustering	Simple Clustering	Pairwise comparisons grow fast	$O(n^2)$	Low

Optimization	Basic Iterative Adjustment	Steady or moderate growth	$O(n)$ or $O(n \log n)$	Moderate
--------------	----------------------------	---------------------------	-------------------------	----------

3.2 Results from Sorting Algorithms

There were evident differences in behaviour of sorting algorithms. Bubble Sort in a step-by-step comparison and swapping form revealed that the number of operations only increases exponentially with the input size. Small examples confirmed that doubling the number of elements caused the operations to increase by about four times, supporting the $O(n^2)$ complexity derived mathematically. Merge Sort on the other hand showed a more even growth rate. Its operations increased in a more moderate way by splitting into small parts and joining these parts in stages. Its $O(n \log n)$ behaviour was checked by simple calculations. Merge sort A divide-and-conquer sorting algorithm like Merge Sort is represented mathematically as follows:

$$T(n) = aT\left(\frac{n}{b}\right) + f(n) \quad (1)$$

the Master Theorem as it is commonly called. This recursiveness formulates the division of the problem into subproblems of size n/b , the number of such subproblems (a) and the extra work done outside of the recursive calls ($f(n)$). Applying this theorem to Merge Sort, where $a=2$, $b=2$, and $f(n)=n$, directly yields the well-known time complexity $T(n)=\Theta(n \log n)$

These experiments demonstrate that mathematical step analysis is adequate to demonstrate the reason some sorting algorithms run faster than others.

3.3 Efficiency Results for Simple Grouping and Optimization Procedures

The growth patterns of the algorithms employed in the grouping or simple optimization were also understandable. As an illustration, a simple clustering process in which every item is compared to all the others exhibited a natural growth in the total operations which indicated a trend of $O(n^2)$. However, by contrast a simple optimization strategy based on repeated updates of a value (as with a simple iterative improvement strategy) exhibited moderate operation increases, tending to scale as $O(n)$ or $O(n \log n)$ with the number of iterations. These findings affirm that a simple mathematical reasoning is capable of providing credible information on the workability of these algorithms.

3.4 Example-Based Verification Outcomes

Small numerical examples were used to ensure that the mathematical predictions were consistent with the real behaviour. As an example, there was a simple dataset of 5, 10 and 20 elements that were tested to verify the number of steps that each algorithm took. The number of observed steps was in the same pattern as that of the mathematical analysis. The steps taken by Linear Search were proportional to the increase in input, the number of operations that Bubble Sort increased fourfold when the input doubled, and the operations of Binary Search increased by very small amounts. These findings confirmed that the mathematical estimates were right. To further exemplify such trends, Table 2 summarizes the number of steps required to solve the problem with small inputs.




Table 2. Approximate Step Count Values for Small Input Sizes


To illustrate these patterns more clearly, the approximate step counts for small input sizes are summarized in Table 2.

Table 2. Approximate Step Count Values for Small Input Sizes

Input Size (n)	Linear Search Steps	Binary Search Steps	Bubble Sort Steps	Merge Sort Steps
5	5	3	10–15	8–12
10	10	4	45–55	25–30
20	20	5	180–210	50–60

3.5 Comparative Analysis of Algorithm Performance

In the comparison of the analyzed algorithms, it turned out that there is an obvious and clear hierarchy of efficiency depending on the mathematical growth patterns. Algorithms with logarithmic or near-linear growth, like the Binary Search and the Merge Sort, were the fastest growing ones since their operations were slow even with the increasing size of the input. Intermediate efficiency was found in algorithms with a linear or slightly super-linear behaviour such as Linear Search and simple iterative optimization techniques with constant but controllable growth in computational steps. Conversely, the most inefficient algorithms were the quadratically growing ones, e.g. Bubble Sort and some simple clustering algorithms, whose number of operations increased exponentially in the size of the input. This general comparison shows that there is a significant difference between the algorithms in the scaling behavior and the mathematical evaluation procedures employed in the current study were more-than-sufficient to represent and demonstrate the differences in performance. Comparison of error behaviour in simple datasets is illustrated based on examples as shown in Figure 3, which indicates that performance is varied between algorithms.

**Figure 3. Illustration of Error Rate Differences Across Four Example Datasets**

The relative efficiency ranking of the analyzed algorithms is presented in Table 3.

Input Size (n)	Linear Search Steps	Binary Search Steps	Bubble Sort Steps	Merge Sort Steps
5	5	3	10–15	8–12
10	10	4	45–55	25–30
20	20	5	180–210	50–60

Table 3. Comparative Performance Ranking of Analyzed Algorithms

In general, according to the results, simple mathematical tools, counting steps, simple complexity notation, and small example work are sufficient to learn and prove the efficiency of algorithms. The results enable a clear picture of how algorithms act as predictable functions with an increase in input size and that the mathematical efficiency models are appropriate in showing those behaviours. The findings also show that choosing the right algorithm to compute the task is also important because the difference in the growth patterns can also have a drastic impact.

4. Discussion

The findings of the research paper support the significance of mathematically based methods to test the efficiency of an algorithm, particularly in a field where computational complexity has a strong impact on performance rates. These results are validated by the modern studies in clustering and optimization, showing that more complex algorithms such as multi-objective evolutionary clustering have higher computational complexities because of the high frequency of pairwise comparisons and network-level dependencies [16]. This is in line with the behaviour of quadratic-growth algorithms which was observed in this study and which exhibited steep growth in the operation counts with increasing input size.

Extended efficiency measurement systems justify the necessity of systematic analytical review too. Data envelopment analysis reviews point to the fact that the concept of efficiency assessment has been developed over decades to compare hierarchical multi-level systems with a strong focus on the central role of mathematical modelling in reflecting the differences in performance [17]. Such agreement between such frameworks and the mathematical validation used in the current study indicates that simple analytical tools still can be used in order to get meaningful insights into the effectiveness of an algorithm.

The behavioural patterns observed in this work are also more reminiscent of mathematics modelling research, especially the work on the simulation of logistic growth, where modelling decision making has a major impact on the accuracy and scalability of the predictions [18]. These similarities support the usefulness of transparent mathematical reasoning in the analysis of growth patterns akin to those of algorithmic complexity.

The findings of the study are also supported by the insights of the complexity theory. The modern discourse of theoretical underpinnings of complexity holds that computational growth has to be comprehended to make informed choices in AI-based and systems-based settings [19]. These theoretical principles are consistent with the validation of logarithmic, linear and quadratic behaviours observed here as well as highlighting the importance of the practical significance of choosing algorithms with good growth properties.

More generalisable efficient algorithm design can also be seen in applied machine learning studies, e.g. injury prediction in sports, where computationally efficient models increase real-time prediction and decision-making [20]. On the same note, development of high-performance computing and big data show the need to have scalable algorithms that can process large datasets that grow in size and are rapidly growing [21]. These are some of the examples that can be used to complement the findings of the study by illustrating that mathematically efficient algorithms are essential in ensuring performance in data-intensive environments.

Recent research in education can also support the pedagogical implications of this work. The research on algorithmic thought is focused on the idea that the knowledge of the structure of algorithms and patterns of their growth facilitates further conceptual

learning in mathematics and computing [22]. The mathematical reasoning (simplified) applied in this research is very much in line with these pedagogical suggestions.

Further comparative analysis of the classification algorithms in different conditions of data complexity also supports the fact that the performance of the algorithm is strongly dependent on its structural design and computational requirements [23]. This is corroborated by the fact that the study discovered that efficient algorithms especially those in the logarithmic and the linear-logarithmic classes exhibited stable growth even with an increase in the size of inputs.

Massive modelling studies also substantiate the finding that modelling paradigms vary greatly in both scalability and computing cost, which reflects the performance gap across algorithmic classes that was found across this study [24]. On the same note, cooperative studies on optimization demonstrate that the structural complexity of the algorithms has a substantial impact on the computational efficiency, which supports the significance of the algorithms in the reduction of the operation overhead [25].

Hierarchical efficiency measurement frameworks also provide more confirmation that well-constructed evaluation strategies can be effective to find the performance strengths and weaknesses of multi-level systems in a reliable manner [26]. This paper finds these insights consistent with the results that indicate that structured step analysis is an effective technique to distinguish between efficient and inefficient algorithms.

The emphasis on algorithmic growth behaviour has also been supported by recent activity on the performance measures of feature selection algorithms, which have demonstrated that appropriately defined measures allow more valuable comparisons across a wide range of computational contexts [27]. Lastly, research that uses enhanced genetic algorithm in modelling education also further proves that the efficiency of algorithms has a direct positive improvement on the accuracy of in analyses and predictive reliability [28]. The close correspondence between the current results and the existing literature, supports the usefulness of clear, non-secret, and mathematically justified assessment procedures of studying algorithmic behaviours in computational data science.

5. Conclusion

This paper has aimed at giving an efficient mathematical validation of algorithmic efficiency using basic analytic tools instead of sophisticated computational systems. The study showed that it was possible to make meaningful distinctions between efficient and inefficient algorithms using transparent and relatively easily reproducible mathematical procedures by counting the number of steps taken by simple algorithms, using a simple notation of complexity, and by proving the existence of an example by experimentation. The observed classifications, including logarithmic, quadratic growth, and so on, are both theoretical know-better expectations present over many years, as well as are consistent with recent empirical and optimization-oriented research with a focus on scalability, adaptability, and computational economy in a wide range of application fields. The comparative analysis highlights that the performance of algorithms is very delicate to the design of the structure: an algorithm like Binary Search or Merge Sort can be used to achieve a steady and predictable growth, whereas the operational steps in other algorithms like Bubble Sort or naive clustering increase rapidly, restricting their application to large datasets. These results confirm the general rule that the correct choice of algorithms is key to making the application computationally viable, and data-driven domains that regularly algorithmically process growing amounts of data. The similarity of the outcomes of simplified analytical methods with mathematical forecasting and the results of examples also represents the methodological efficiency of simplified analytical techniques. In general, the paper confirms that foundational mathematical

reasoning is still an effective instrument in the analysis of algorithmic behaviour that can be used to achieve pedagogical and practical decisions. Giving a clear and repeatable model of efficiency assessment, this work forms part of the current work on intermediating what can be theorized and what can be computationally difficult, which is to further study computationally light methods of assessing algorithms.

References

1. Antonov and V. Voevodin, The algorithms properties and structure study as a mandatory element of modern IT education, In: Russian Supercomputing Days, Springer International Publishing, Cham (2020), 524-535.
2. Anuradha and T. Velmurugan, A comparative analysis on the evaluation of classification algorithms in the prediction of students performance, Indian Journal of Science and technology, 8, No 15 (2015), 1-12.
3. E. Jacob, N. Ashodariya and A. Dhongade, Hybrid search algorithm: Combined linear and binary search algorithm, In: 2017 International Conference on Energy, Communication, Data Analytics and Soft Computing (ICECDS), IEEE, (2017), 1543-1547.
4. E. Taiwo, A. O. Christianah, A. N. Oluwatobi and K. A. Aderonke, Comparative study of two divide and conquer sorting algorithms: quicksort and merge sort, Procedia Computer Science, 171, (2020), 2532-2540.
5. F. Liu and D. Panagiotakos, Real-world data: a brief review of the methods, applications, challenges and opportunities, BMC Medical Research Methodology, 22, No 1 (2022), 287.
6. G. Mohammadi, M. H. Amini and H. R. Arabnia, Evolutionary computation, optimization, and learning algorithms for data science, In: Optimization, Learning, and Control for Interdependent Complex Networks, Springer International Publishing, Cham (2020), 37-65.
7. G. Mohammadi, M. H. Amini and H. R. Arabnia, Evolutionary computation, optimization, and learning algorithms for data science, In: Optimization, Learning, and Control for Interdependent Complex Networks, Springer International Publishing, Cham (2020), 37-65.
8. García-Jiménez, J. J. Torres-Gordillo and J. Rodríguez-Santero, Factors associated with school effectiveness: Detection of high-and low-efficiency schools through hierarchical linear models, Education Sciences, 12, No 1 (2022), 59.
9. H. Zenil, A review of methods for estimating algorithmic complexity: Options, challenges, and new directions, Entropy, 22, No 6 (2020), 612.
10. Hernandez and T. B. Brown, Measuring the algorithmic efficiency of neural networks, arXiv preprint arXiv:2005.04305, (2020).
11. J. L. Fernández-Martínez, Z. Fernández-Muñiz, A. Cernea and A. Kloczkowski, Predictive Mathematical Models of the Short-Term and Long-Term Growth of the COVID-19 Pandemic, Computational and mathematical methods in medicine, 2021, No 1 (2021), 5556433.
12. J. López-Fernández, E. Guerra and J. de Lara, Example-based validation of domain-specific visual languages, In: Proc. 2015 ACM SIGPLAN International Conference on Software Language Engineering, (2015), 101-112.
13. Lin, Binary search algorithm, WikiJournal of Science, 2, No 1 (2019), 1-13.
14. Mala and R. Ali, The Big-O of mathematics and computer science, Journal of Applied Mathematics and Computation, 6, No 1 (2022).
15. Mohammadagha, Hybridization and Optimization Modelling, Analysis, and Comparative Study of Sorting Algorithms: Adaptive Techniques, Parallelization, for

- Merge sort, Heapsort, Quicksort, Insertion Sort, Selection Sort, and Bubble Sort, (2025).
16. Orouskhani, D. Shi and Y. Orouskhani, Multi-objective evolutionary clustering with complex networks, *Expert Systems with Applications*, 165, (2021), 113916.
 17. Panwar, M. Olfati, M. Pant and V. Snasel, A review on the 40 years of existence of data envelopment analysis models: historic development and current trends, *Archives of computational methods in engineering*, 29, No 7 (2022), 5397.
 18. Pelagalli, S. Faccio and P. Casari, Mathematical Modelling and Simulation of Logistic Growth, *Applied Sciences*, 15, No 8 (2025), 4409.
 19. Qudrat-Ullah, Theoretical Foundations of Complexity, In: *Navigating Complexity: AI and Systems Thinking for Smarter Decisions*, Springer Nature Switzerland, Cham (2025), 11-38.
 20. Rossi, L. Pappalardo and P. Cintia, A narrative review for a machine learning application in sports: an example based on injury forecasting in soccer, *Sports*, 10, No 1 (2021), 5.
 21. S. Gathu, High-performance computing and big data: Emerging trends in advanced computing systems for data-intensive applications, *Journal of Advanced Computing Systems*, 4, No 8 (2024), 22-35.
 22. S. T. Muxtaraliyevich, ALGORITHMIC THINKING IN MATHEMATICS: A PEDAGOGICAL FRAMEWORK FOR DEEP CONCEPTUAL LEARNING, *Modern American Journal of Linguistics, Education, and Pedagogy*, 1, No 3 (2025), 587-594.
 23. Scholz and T. Wimmer, A comparison of classification methods across different data complexity scenarios and datasets, *Expert Systems with Applications*, 168, (2021), 114217.
 24. Schweiger, H. Nilsson, J. Schoeggl, W. Birk and A. Posch, Modelling and simulation of large-scale systems: A systematic comparison of modelling paradigms, *Applied Mathematics and Computation*, 365, (2020), 124713.
 25. W. Deng, H. Zhao, L. Zou, G. Li, X. Yang and D. Wu, A novel collaborative optimization algorithm in solving complex optimization problems, *Soft Computing*, 21, No 15 (2017), 4387-4398.
 26. W. Li, W. D. Cook, Z. Li and J. Zhu, Efficiency measurement for hierarchical situations, *Journal of the operational research society*, 72, No 3 (2021), 654-662.
 27. W. Mostert, K. M. Malan and A. P. Engelbrecht, A feature selection algorithm performance metric for comparative analysis, *Algorithms*, 14, No 3 (2021), 100.
 28. Y. Yang, Quality evaluation method of a mathematics teaching model reform based on an improved genetic algorithm, *Scientific Programming*, 2021, No 1 (2021), 6395349.