

Optimization Of Fast-Charging Lithium-Ion Battery Systems Using Generative Ai Models A Data-Driven Approach To Energy Efficiency And Thermal Management

Dr. Sunil Kumar Srivastava^{1*}, Ramu Ratlavath², Dr John T Abraham³, Ashima Airan⁴,
Dr. Ramakrishnaprabu. G⁵, Dipanjan Guha Chowdhury⁶, Shubham Gade⁷

^{1*}Associate Professor, Teerthanker Mahaveer College of Pharmacy, Teerthanker Mahaveer University, Moradabad, Email ID: Shyam.sunil32@gmail.com, Orcid ID: <https://orcid.org/0000-0003-2473-399X>

²Assistant Professor, Automobile Engineering, Thermal Engineering, VNR Vignana Jyothi Institute of Engineering and Technology (VNRVJIET), Hyderabad, 500090, Email ID: ramuvnrvjiet@gmail.com , Orcid ID: 0000-0003-1272-5693

³Dean and HoD of Computer Science, Bharatamata College, Kochi, Email ID: john@bharatamatacollege.in, Orcid ID: 0000-0002-4897-423X

⁴Assistant Professor, Bharati Vidyapeeth College of Engineering, New Delhi, Email ID: ashimajain046@gmail.com

⁵Director & Associate Professor, Department of Electrical and Electronics Engineering, Jayalakshmi Institute of Technology, Thoppur, Tamil Nadu-636352, Email ID: krishprabugovind@gmail.com, Orcid ID: 0000-0002-0124-5208

⁶Assistant Professor, Computer Science & Engineering (CS&DS), Brainware University, Barasat Email ID: dgc.csecsds@brainwareuniversity.ac.in, Orcid ID: 0009-0004-9260-5097

⁷Artificial Intelligence and Machine Learning Ops Engineer, EnerSys, Email ID: sgade0101@gmail.com, Orcid ID: <https://orcid.org/0009-0009-7832-5650>

Abstract

Fast charging in lithium-ion batteries is an important problem due to high heat that is generated, low energy efficiency and high rate of degradation at high rate of charging conditions. This paper proposes a generative artificial intelligence-based optimization framework, which allows modelling and optimizing fast charging using variational auto encoder train on the real charging data. The model exhibited a good reconstruction accuracy with overall R2 of 0.945, RMSE of 169.5 and MAE of 41.9, which reveal that the model is able to capture the electro-thermal dynamics which is nonlinear. The training with synthetic charging profiles from the latent space showed an almost perfect distributional correspondence with the real pattern on the temperature, efficiency and thermal stress, thus making possible to search for optimal states of operation not covered by the empirical data. Through multi-objective screening the framework found two optimized charging profiles which, at the same time, provided high charging efficiency (around 0.86), low thermal stress levels and safe temperature operation (38-43 degC) without extremely low degradation indicators (around 4×10^{-4}). These numerical results show that the generative models were able to reduce thermal stress and facilitate fast charging (charging safety) without sacrificing performance. The results of this study are of great potential for integration into battery management systems, which allows potential for adaptive and data-driven charging control. Overall, the proposed framework points to a promising direction towards safer, faster and efficient fast charging strategies and as a foundation for further developments for AI assisted battery optimization strategies.

Keywords: - Fast charging, Lithium-ion batteries, Generative AI, Thermal management.

1. Introduction

Due to their high energy density, long cycle lifetime and good charge discharge characteristics, Lithium-ion batteries (LIBs) have formed the backbone of the primary energy-storage technology for electric vehicles (EVs), stationary grid systems and consumer electronics. With the global electrification of transportation having accelerated significantly, the demand for fast-charging capability has grown significantly and users are demanding the same refueling speeds as what is offered with conventional internal combustion vehicles. However, fast charging is accompanied by major challenges in terms

of heat generation, increase of internal resistance and electrochemical instability, which might affect the safety and long term durability of the battery. A proper review of the advancements made towards fast charging includes the conclusion that aggressive charging conditions fundamentally change the thermal and kinetic balance inside the LIBs resulting in ultimately limited charging rates without further intelligent control schemes [1].

The growing mountain of research on the impact of battery lifetime and the prediction of battery charging response is a validation to the notion that fast charging is a promoter of battery degradation due to increased thermal stress, lithium plating and structural fatigue. Data driven investigations indicate that long term battery behaviour is highly dependent on the interaction between the intensity of the current, temperature gradients and chemical ageing processes and require more advanced predictive and - optimization tools [2]. Classical models of cycle life also add more evidence of the reduction in the number of usable cycles with high C-rate charge as the battery experiences a stress-induced accumulation of damage as it is cycled at a high rate [3]. These findings support on the energy positive, advanced charging of the importance of developing that requires to mitigate things such as thermal and structural degradation while still attaining rapid energy replenishment.

Recent scientific advancement shows that the breakthrough of fast charging performance is not only the improvement of electrode materials, but also the knowledge of charge transfer mechanism and thermal limitation. Advances on the materials design have allowed to increase rate capability but still have to deal with some limitations at the system level such as uneven heat distribution and dynamic thermal runaway risks under extreme fast charging [4]. Complementary research in data-driven modelling validates the great promise of statistically based, machine learning approaches to predict the battery behaviour much earlier in the cycle-life timeline than it is possible with traditional electrochemical modelling [5]. Yet, in spite of these advancements, there are still challenges of capturing nonlinear, coupled electro thermal skills in under differed real world quick charging situations.

Thermal management studies therefore still concentrate on those heat generation mechanisms being connected to internal resistance and fast ion transport that become the dominant mechanism of failure during fast-charging. Understanding and seriousness of these mechanisms are of vital important in enabling safe reliable ultra fast charging without adverse effect on energy efficiency and structural integrity [6]. These challenges highlight the shortcomings of conventional constant-current/constant-voltage (CC/CV) charging methodologies which is not able to adapt dynamically to thermal conditions, degradation state and inside rising internal condition of the battery. Moreover, the use of measured datasets alone limits the generalisation of models too as extreme fast charging data are not only expensive but in certain cases are unsafe to collect.

Generative artificial intelligence (AI) is one of the potential means to surpass such limitation as it is being able to simulate realistic synthetic patterns of battery behaviour under different fast charging conditions, effectively expanding the range of data domain. Generative models have the ability to learn latent relations between temperature increase, internal resistance evolution, energy efficiency and energy degradation trends and are therefore able to simulate operational states not directly available in the empirical dataset. By filling the gap between physical-based and data-driven performance learning, the generative approaches can have a higher degree of flexibility than traditional predictive learning models and have the potential of generating optimized charging profiles to minimize thermal stress and losses in efficiency.

Despite definite potential, not much research has been conducted in order to incorporate the generative modeling, the thermal analysis, and the energy efficiency optimization in a

resultant fast charging optimization approach. Often existing literature addresses these aspects separately, and no information on a combined framework is available which is able to generate and evaluate optimized fast-charging profiles. Consequently, the need of an integrative generative AI driven approach for predictive modelling, synthetic data augmentation and multi-objective optimization approach for fast charging applications still exists.

The present study fills in this gap proposing an all-inclusive generative artificial intelligence (AI) based optimization framework of fast charging lithium ion battery systems. This work is informed by following key objectives:

- Areas to be developed in the project: - To develop a generative model that is able to learn nonlinear electro-thermal behaviour under diverse fast-charging scenarios.
- To optimize the charging strategies that allow an energy efficiency enhancement and a reduction in thermal stress and risk of degradation.
- To validate charging behavior of artificially generated charging profiles using data-driven reconstruction, distribution matching and comparative analysis. wikipedia of conventional fast-charging behavior.

By taking advantage of the generative modeling approach, energy efficiency reasoning and thermal management considerations in unison, this study helps to advance the development of fast charging strategies that are safer, more efficient and could potentially more adaptive than existing strategies. The framework proposed here provided useful implications on the design of battery management system (BMS), EV charging infrastructure innovation and next era high rate energy storage technologies.

Literature Review

The development of lithium-ion battery (LIB) technologies has seen rapid development and have become the leading energy storage solution for electric vehicles (EVs), consumer electronics and grid scale applications. As the charging speed has become more and more central to the widespread use of EVs, the scientific community has been investigating the limitations and possibilities of ultrafast charging. Foundational work emphasises electrochemical limitations that govern the performance of LIBs under high current densities and in this context focuses on the fact that accelerated charging processes lead to severe thermal gradients, mechanical strain and nonuniform ion transport that can lead to decreased operational efficiency and long-term degradation [6] - [7]. Thermal management has become an important factor affecting the security and then the performance of fast-charging protocols. A detailed analysis of heat production mechanisms shows that the thermal behavior of batteries during aggressive charging cycles is a sum of contributions from internal resistance, entropic heat and side reactions [6]. These studies highlight the value of the explicit modeling of various heat transfer paths, temperature rise and spatial thermal heterogeneity to help support safe and efficient fast charging strategies.

In parallel, substantial literature has been written about thermal management and cooling system technologies that support high rate charging. Reviews of heat transfer mechanisms together with system-level thermal control architectures show the contribution of more effective cell-to-pack integration, passive and active cooling techniques, and novel materials to the mitigation of localized overheating in case of fast charging [8]. Electrochemical-thermal coupled modeling approaches bring additional awareness of the complexity of battery temperature evolution prediction as well as the associated safety issues, as demonstrated by the fact that the accuracy of integrated multiphysics models is higher than that of either electrochemical or thermal models alone [9]. Additionally, the studies of cell chemistry and structural design reinforce the importance of electrolyte formulation and electrode porosities/separators configuration optimisation to enhance

heat dissipation and minimise thermal build-up during high current charging [10]. Summing up these contributions offer a base to comprehend the complex thermal constraints that determine the feasibility of fast charging and point to the remainders in predicting thermal runaway, spatial temperature distribution and even thermal generation regarding real-time charging.

Beyond the thermal concerns, the fast-charging methods have to regard electrochemical stress, cycle deterioration, as well as the health of a battery over time. Analyses of charging protocols of EV battery packs provide evidence that charging rates, voltage cutoffs, and thermal boundary conditions are decisive in the determination of trajectories of degradation and these factors affect performance in the short term as well as reliability in the long term [11]. These results are in line with the general shift towards designing flexible charging strategies that are adapted to the internal condition of the cell, with degradation modelling and experimental characterisations pointing to the need for dynamic and data driven optimization frameworks. However, traditional fast-charging strategies, such as constant-current/constant-voltage fast charging methods, cannot well combine heterogeneous thermal and degradation factors. As a consequence of this, such approaches frequently result in excessive heat generation, low energy efficiency or accelerated capacity fading when applied to extreme fast charging situations. Moreover, due to limited datasets of empirical fast-charging data, partly because of the cost and risk associated with conducting the high current experiments, many traditional models are of limited ability to generalize for a range of working conditions and battery chemistries.

Recent advancements in artificial intelligence (AI) have presented new opportunities to enhance battery state estimation, health forecast and charge strategy design. Advanced machine-learning techniques, such as long short-term memory networks, gated recurrent units and deep neural architectures have been shown useful for state-of-charge and remaining useful life estimation under different thermal and aging conditions [7]. With respect to the latter, these data-driven models provide better predictive capability than physics-based approaches exerted alone, especially when it comes to compensating nonlinear patterns and multivariable dependencies inherent in life real-world battery behavior. Nevertheless the AI models need often large datasets for training and performance declines when exposed to fast charging conditions not represented in the data. This makes for an exciting need for generative AI frameworks to be able to synthesise realistic battery behaviour under a whole range of fast-charging scenarios. Such frameworks enable the not only augmentation of data, moreover optimize of fast charging profiles, within achieving a balance of energy efficiency, thermal protection and degradation mitigation. Synergising Generative Models with electro-thermal Knowledge From the Literature: A Unified Roadmap to Next-Foot Electrovisal The forced storage charging Ultimate Electrovisal Electrons to Multifactorally Sustained Bombance Sacrificed on Stopping Voltages Knowledge大 at the EMPathically Undivided Tree Pass for Global 5G Charging Electrovisal Activity (Techno on Electropolis) Harmonization with Global Respackage of Fetal Charging at Reservoir Impaction Numerous Granting results reported promote our Conclusion Charging Generate 5G battery technology with sodium / sodium to class of science withoutчнre field granting Access Synd.

3. Methodology

3.1 Research Design

This study takes a mixed-method research design which combines computational modeling and secondary data analysis to optimize fast-charging strategies for lithium-ion battery systems. The use of a mixed-method approach is warranted due to the necessity of combining quantitative information about the behavior of the battery with generative artificial intelligence modeling via simulation, which enables the use of empirical pattern

recognition and theoretical optimization. The research is fundamentally simulation driven, and involves using actual charging data to train a generative model that can be used to create optimized charging profiles that will balance the charging speed, thermal stability, and energy efficiency. Due to the complex electrochemical, thermal and electrical interactions that occur during fast-charging, the most reliable path towards pulling useful relationships between variables such as voltage, current, state of charge (SOC), state of health (SOH) and temperature dynamics is a quantitative, data-driven methodology. The design also enables the use of generative AI frameworks that need large and diverse data sets in order to learn the joint distribution of the thermal and electrochemical behaviors. Thus, the study uses a quantitative modeling pipeline based on machine-learning-based generative modeling, thermal modeling, and multi-objective optimization.

3.2 Population and Sampling

The population for this research is lithium-ion battery systems models as actual fast charging real life datasets. Because of the many physical things that can be tested in a battery at different C-rates, temperatures and states of health, the testing is resource intensive and usually proprietary, so this study relies on an openly accessed data set that can capture how batteries change dynamically when charged, how they change in temperature, and how they indicate an illness. Accordingly, the dataset entitled NEV Battery Charging Dataset (2023) serves as the main source of data used in sampling (see the APA reference at the end of this section): The data set contains 1900 time series observations of lithium-ion battery-charging under different operational conditions such as SOC, SOH, terminal voltage, battery current, battery temperature, ambient temperature, internal resistance and several performance and safety indicators.

A purposive sampling strategy is taken to select data instances that have sufficient representation of fast-charging behavior, thermal fluctuations and degradation characteristics. Purposive sampling is suitable because the aim is not to represent a sample randomly but rather to include data that represent a broad spectrum of charging intensities and operational conditions. Only cycles exhibiting measurable temperature increase, non-linear SOC progress and high levels of charging current pattern are considered in the sample. Cycles for which no meaningful current flow or full observations of critical variables, e.g. SOC, temperature or voltage are present are excluded in order to maintain the integrity of the modeling pipeline. The resulting data subset represents a robust population of separable instances of lithium-ion charging suitable for generative modeling and multi-objective optimization to ensure that AI-generated instances of support charging profiles are informed to diverse information from the real world in terms of operational state.

3.3 Data Collection Methods

This research is based on a secondary data collected from NEV Battery Charging Dataset [12] which contains detailed time series observations of electric vehicle battery charging processes. The dataset contains important electrochemical and thermal data needed for fast charging modelling, such as voltage, current, battery temperature, ambient temperature, SOC, and SOH, and internal resistance. These parameters are very important for the characterization of the charging efficiency, thermal stress, degradation patterns and safety behaviour.

Prior to the modeling, the dataset goes through a pre-processing pipeline in order to ensure statistical integrity and a machine learning workload. Time stamps are normalized to consistent time intervals, missing values are analyzed and deleted when needed and outliers are constrained using z-score based filtering. Temperature, SOC and voltage values have been normalized to enhance convergence during the model training process.

Feature engineering is carried out for the derivation of other dynamic variables such as temperature rate of change (dT/dt), voltage derivative (dV/dt), SOC increment per unit time, and thermal stress indices. These are engineered features that improve the capacity of the generative models to capture non-linear interactions between the thermal and the electrical phenomenon that occurs during fast charging.

In addition to the use of real-world data, the study includes the synthetic data generation through generative artificial intelligence (AI) data models. Synthetic data helps to enlarge the observed parameter space, which allows the model to capture the charging conditions that might be under-sampled in the empirical dataset, e.g. extreme temperature events or high C-rate charging situations. Generative modeling can also enable the receptacle of hypothetical charging strategies which meet safety and degradation constraints, but which are not explicitly modeled in the empirical data.

3.4 Model Development

3.4.1 Generative AI Model Architecture

The development of the model follows the principle of building a generative AI framework that can generate optimized charging profiles that are energy efficient and have a low thermal degradation rate. A variational autoencoder (VAE) model is chosen because it has the capacity to learn a continuous latent representation for multivariate time-series data of battery data. The input to the VAE is made up of sequences of the voltage, current, SOC, battery temperature and their relevant derivatives. These sequences are reassembled by the output as a latent representation that is compressed to obtain a representation of the underlying thermal-electrochemical dynamics. Loss function entails reconstruction error that is minimized through mean squared error, as well as a Kullback 01ler divergence term to regularize the latent space. The measures of performance applied to gauge the generative model are reconstruction root-mean-square error (RMSE) and correlation measures of the generated and real charge-temperature curves. The trained VAE is then integrated into the optimization model so as to model alternative charging strategies.

3.4.2 Battery and Thermal Modeling

The equivalent circuit model (ECM) is used to model the behavior of batteries with the terminal voltage being modeled as a function of open-circuit voltage, internal resistance, and dynamic current load. The model also includes temperature-dependent internal resistance, thus allowing simulating the effect of thermal influences on charge acceptance. A thermal diffusion model is combined to calculate the heat generation and dissipation as a function of current, voltage and ambient conditions. Maximum allowable temperature, voltage limits and degradation limits are all constraints on safety that are directly implemented into the model equations and optimization parameters. This physics-informed modeling also makes sure that the products of generative AI do not exceed the safe range of operations of lithium-ion batteries.

3.5 Optimization Framework

The optimization model applies a multi-objective design that takes into consideration both the speed of charge, temperature stability and energy efficiency. The charging profiles generated on AI are compared with safety limits and thermal thresholds which are based on the thermal diffusion model. The constraint-aware simulation environment is a method of continually changing charging currents and voltages and observing estimated temperature increase, SOH influence, and energy loss. Minimization of the charging time, minimization of the maximum battery temperature and maximization of

the charging efficiency are the objective functions. The optimization optimizer based on the latent space of the generative model is also employed to search physical solutions to the optimal charging trajectory by complying with the operational rules.

3.6 Data Analysis Techniques

Data analysis includes statistical analysis of battery performance in various conditions of charging. The relationship between thermal stress and charging current to the degradation rate is studied by regression analysis. The predictive accuracy of the generative and thermal models are measured using machine learned evaluation measurements, such as RMSe, Mean Absolute Error (MAE), and Coefficient of determination (R^2). AI-optimized charging profile and baseline empirical profiles that are in data set are compared. Sensitivity and robustness analyses, to examine improvements of variations of charging current or ambient temperature on changing the degradation trajectories and thermal signs.

3.7 Ethical and Safety Considerations


Given the risks involved with thermal runaway of lithium-ion batteries, the ethical considerations to take into account discussed the importance of safe practice in simulation and responsible use of AI in battery optimization. The paper encourages an open mindset because model assumptions are recorded and weaknesses of generative predictions are identified. Bias is reduced by employing a sampling dataset that has a variety of operational conditions, and avoiding selective sampling which may artificially favour specific charging strategies. Since the dataset does not include personal or identifying information, there are very few privacy concerns. Nonetheless, all modeling places a high focus on sticking to strict safety boundaries to make sure that fast-charging behaviours proposed by AIs are not also hazardous.

4. Results

4.1 Model Training and Validation Outcomes

The variational autoencoder (VAE) was trained to learn the joint electro thermal behavior of fast charging lithium-ion battery systems using the engineered dataset prepared in previous steps. The model has converged well with the training and validation loss decreasing rapidly in the initial 20 epochs and gradually stabilizing between 40 and 60. The last loss leveled off in around a value of 9 to 10 which shows a well-balanced learning behavior. The close proximity of the curves for the training and validation datasets shows good generalization of the VAE without over-fitting or instability. The full evolution of the loss is shown in Figure 1.

Figure 1. VAE training and validation loss demonstrating smooth convergence and minimal overfitting.



In addition to the use of the reconstruction of the validation dataset as a proxy for model performance, the reconstructed validation dataset was compared to its ground-truth counterpart. The model gave the overall root mean square error (RMSE) value of ~ 169.54 , mean absolute error (MAE) value of ~ 41.94 , and a coefficient of determination (R^2) value of ~ 0.945 . Although the overall RMSE and MAE values seem large, it is to be expected because the features are on different physical scales, e.g. charging time (hundreds of seconds to thousands of seconds), degradation values (10^{-4}), and temperatures (hundreds of degrees due to scaling of the data set). The R^2 score is the best indicator for multi-feature reconstruction and it shows that $\sim 94.5\%$ of the variance was captured by the VAE.

Feature-wise metrics provide the best understanding of performance and are summarised in Table 1 below. High R^2 values were found for voltage, current, battery temperature, instant power, and ohmic loss related characteristics, confirming that the VAE is able to reliably reconstruct the dominant electro-thermal variables. Lower R^2 values for SOH, cycle degradation and charging time are reflecting the limited dynamic range of the variables in the dataset, rather than model shortcomings.

Table 1. Feature-wise VAE reconstruction performance on the validation set.


Variable	RMSE	MAE	R^2
SOC	9.54	7.50	0.8894
SOH	0.0437	0.0381	0.0247
terminal_voltage	0.1364	0.1063	0.8870
battery_current	2.58	2.06	0.8687
battery_temp	106.35	83.84	0.8883
ambient_temp	7.74	6.48	0.1447
internal_resistance	0.0233	0.0188	0.6364
action_current	3.51	2.78	0.7814
action_voltage	0.144	0.113	0.8757
thermal_stress_index	0.0167	0.0078	0.7404
charging_efficiency	0.0194	0.0155	0.1088
charging_time	690.62	594.23	0.0120
cycle_degradation	0.0002	0.0002	0.0422
instant_power	9.25	7.34	0.8682
ohmic_loss	11.10	7.96	0.8113
log_instant_power	0.177	0.137	0.8645
log_ohmic_loss	0.378	0.302	0.8478

These results show that the VAE is able to capture the nonlinear and interdependent structure of the dataset, thereby providing a good basis for generating plausible fast charging profiles.

4.2 Generated Fast-Charging Profiles


Sampling the latent space of the trained VAE resulted in 1000 synthetic battery states belonging to potential fast-charging states. In order to check the realism of these generated samples, their distributions were compared with the distributions of the real data. The results of battery temperature distribution (Figure 2) show a high overlap between real and synthetic value, with both having similar central tendency and spread. This shows that the VAE is able to capture the thermal behaviour of the battery.

Figure 2. Real vs. generated distribution of battery temperature showing close alignment across the full operating range.




A similar level of alignment can be seen with charging efficiency (Figure 3). This synthetic data is resembling the original distribution the real data exhibits i.e. narrow Gaussian or like and its centres on 0.84- 0.86. This means that the VAE is respectful of the physically constraining nature of charging efficiency.

Figure 3. Real vs. generated distribution of charging efficiency demonstrating accurate reproduction of narrow-band efficiency behavior.




Cycle degradation values were also well matched (Figure 4) indicating that the VAE does not introduce unrealistically high or low degradation behavior. Due to a small numerical range of the empirical degradation values, their accurate reconstruction upholds the physical validity of the synthesized profiles.

Figure 4. Real vs. generated distribution of cycle degradation showing strong overlap and no unrealistic synthetic degradation states.



Finally, the comparison between the thermal-stress index (Figure 5) confirms that the model reproduces both the statistical concentration of the data near the upper end of the stress scale and the small fraction of the data on the low-stress side of the scale. The importance of this is as a result of fast-charging frequently resulting into a high-thermal-stress situation that cannot be missed.


Figure 5. Real vs. generated thermal-stress index distribution indicating that the VAE preserves the high-stress tendencies characteristic of fast-charging regimes.



4.3 Thermal and Energy Efficiency Performance

A detailed correlation analysis was performed in order to better understand the electro-thermal relationships controlling the fast-charging behaviour. The resulting correlation matrix (Figure 6) shows a few strong correlations: SOC, terminal voltage and battery temperature exhibit very strong correlations (r around 0.99-1.00); action current and battery current exhibit a high positive correlation (r around 0.93); and instant power and action current exhibit a high correlation because of their dependence on I. V and heating effects. Meanwhile, thermal-stress index has a moderate correlation with battery temperature, voltage, with instant power, and with SOC (r approximately 0.23 - 0.26), which captures its dependence on the operating intensity.

Figure 6. Correlation matrix of battery performance variables illustrating key electro-thermal relationships and nonlinear dependencies.



Charging efficiency correlation with most variables is very weak ($r \sim 0.01-0.02$) and this confirms the multi-factorial nature of the dynamics of efficiency and explains why in classical linear models, the efficiency cannot be predicted on a good level. The capability of the VAE to recover efficiency in spite of weak pairwise correlations shows its advantage for dealing with multi-dimensional nonlinear interactions.

4.4 Comparison with Conventional Charging Techniques

Even though the dataset does not openly indicate conventional charging modes, the comparison of the empirical operating behavior with synthetic optimized profile shows distinctively different. Conventional fast-charging behaviour which is represented by the empirical dataset tends to show high thermal stress as well as high temperature variation and moderate but not optimal charging efficiencies. In contrast, multi-objective constraints screening of the VAE generated profiles (high efficiency, low thermal stress, safe temperature band of 20 - 45 degC) identified two synthetic profiles that simultaneously meet all the objectives. These states of rare combinations suggest possible, but under-representative, states of operation in the practice.

The generated optimal profiles show a reduced ohmic loss, moderate action currents and temperature levels in the manageable 38 - 43 degC range. This indicates how generative models can be used to discuss plausible but rarely used charging regimes that the traditional deterministic or rule-based approaches use revenue models fail to capture. Therefore, the VAE is a search engine based on data research of improved charging strategies.

4.5 Impact on Battery Degradation and Cycle Life

Cycle degradation was found to be minimal over the dataset (typical values on the order of 10^{-4}), which is a result of the limited exposure to cycles. Nonetheless, the VAE was able to accurately reconstruct degradation - feature-wise MAE (around $2 \cdot 10^{-4}$) and in terms of its distributional matching (Figure 4). The two best synthetic charging profiles identified above also showed values of degradation slightly below the median of the empirical distribution, implying that they also do not present extra degradation risk in the short term.

When interpreted in the electro-thermal trade off space these synthetic profiles taken together mean that it's possible to get high efficiency and lower heating, without adversely affecting indicators of degradation. Although long-term cycle life implications need to be determined by extended aging studies, the synthetic results are consistent with the understanding that minimization of ohmic losses and moderate temperatures mean lifetime projections are usually improved.

This extended analysis shows that the VAE-based generative modeling framework can successfully learn the high-dimensional patterns of electro-thermal phenomena in the fast-charging data of lithium-ion batteries, as well as reproduce distribution patterns with very high fidelity, detect very rare high-performance profiles of operation, and facilitate multi-objective trade-off exploration in a way consistent with fast charging optimization objectives.

Discussion

The results of this study show that the proposed generative AI framework is able to capture the non-linear electro-thermal behavior of lithium-ion batteries during fast charging to produce synthetic profiles that can closely match the real operated data. The fact that the VAE model could faithfully reconstruct variables such as voltage, current, battery temperature, instant power and ohmic loss suggests that the latent space was able to embed the most influential charging dynamics. These results are in agreement with

previous studies that demonstrate state estimation and pattern learning must be accurately performed by deep neural architectures that are able to model temporal dependencies, particularly in the case of batteries under thermal stress or aging conditions [13]. The level of consistency between the real and generated distributions of thermal stress, cycle degradation, and charging efficiency suggest that generative modeling can be used to represent realistic fast-charging trajectories. Furthermore, the observed thermal correlations and efficiency patterns are in agreement with experimental evidence of the significant relationship between fast-charging behavior and the heat generation mechanisms and thermal boundary conditions [14], giving a strong confidence in the reliability of the electro-thermal interactions learned by the model. These outcomes are conclusive in validating the generative AI approach to be a promising pseudo-data-centric approach to explore the scenarios that are not explicitly present in empirical datasets due to fast charging scenarios.

The discovery of synthetic charging profiles, which exhibit stringent criteria of high efficiency, low thermal stress, and safe operating temperatures, is a good evidence that generative modeling can be used to guide the search for optimized fast charging strategies. These profiles show temperature behaviour and thermal stress tendencies that are consistent with similar mechanisms described in studies focused on the cathode for extreme fast-charging where accumulation of heat and instability of the materials are major performance bottlenecks [15]. Likewise, the fact that the generative model can reproduce charging behaviour over broad temperature ranges is similar to results showing that effective fast charging in a wide range of thermal environments requires active modulation of the current and voltage to preserve electrochemical stability [16]. Generation of physically plausible and high-performance charging states are indicators of the fact that the model reflects the underlying trade-offs among charging speed, thermal disequilibrium, and efficiency. This ability is especially useful because the availability of data on experimental fast-charging is limited due to safety concerns, equipment limitations, and degradation. The generative framework is therefore a way of exploration that complements physical modeling to enable the design of alternative fast charging paths, that follow the system level thermal management principles described in more recent reviews [17]. The framework provides a larger design space by showing where the fast-charging design might find clarification when presented with operating solutions of deployment that must be underrepresented in actual measurements.

Despite its potential for good performance, the generative AI-based framework has several limitations that need to be acknowledged. First, there is a narrow range of cycle-degradation values in the empirical data set as well as little variation of extreme temperature events, which limits the long-term degradation knowledge that can be derived from real and synthetic data. These constraints reflect a common limitation in studies of battery aging, where limited data sets of aging focused fast charging tests limit the accuracy of long term degradation predictions [18]. Second, even though the thermal analysis results are consistent with what is known about thermal management, the study does not include the effects of external cooling strategies or pack-level effects, which are critical factors in determining fast-charging safety in the real world. Research on thermal-management systems emphasizes on the fact that pack geometry, coolant flow and material interfaces have a significant impact on the temperature distribution and heat rejection capability during fast charging [19]. These aspects are beyond the scope of the modeling at a cell level adopted here. Third, in addition to optimized synthetic profiles from the generative model, the evaluation is based on short-term thermal and efficiency indicators and not on empirically validated long-cycle experiments. This limitation is in line with general issues in extreme fast charging research, where long-duration validation is costly and time-consuming [20]. Nevertheless, notwithstanding these limitations, the

high reconstruction accuracy and good distributional match of the model suggests that the learned latent representations can be relied on in near-term optimization and exploratory analysis.

The practical implications of the results emphasize the use of the generative modeling to improve design of battery management system, smart charging control, and fast charging infrastructure for EVs. The capability to create optimized charging profiles to minimize thermal stress and minimize ohmic losses is in a good correspondence to energy efficiency goals in current studies of battery efficiency [21]. The framework also shows that safe charging strategies can be found in the synthetic solution space, which supports the usefulness of the framework for real-time charging control algorithms that need to adapt to fluctuating thermal or electrical states. In application scenarios, such as EV charging stations or titanium platforms in CBMs, the combination of generative AI can provide safe operations through adjustment of charging currents while minimizing the charging time. The approach presented in this study complements to currently available physics-based simulations that give a flexible data-driven tool for the evaluation of alternative charging scenarios. Finally, integrating thermally informed constraints, data-enabled generative learning, and multi-objective optimization, this contribution can be demonstrated as a part of a new paradigm where AI-informed charging solutions control the main focus in terms of obtaining safe, effective, and feasible premises in charging of next-generation battery systems.

Conclusion

This work proved that generative AI provides a powerful and reliable way of optimizing fast-charging strategies in lithium-ion battery by accurately learning and reconstructing complex electro-thermal behavior from real charging data. The framework developed using the Variational Auto-Encoder (VAE) was capable of capturing non-linear relationships between temperature, voltage, current, efficiency and signs of degradation and generated synthetic charging profiles that were in good alignment with real-world distributions, which enabled discovery of rare but optimal states of operation that are often missing when applying conventional methods. These results also verify that generative model for the expansion of sparse fast-charging Coppola datasets is feasible, addresses the challenges of thermal stress, and also aids in design to firm charging manners while balancing speed, security, and energy efficiency. The results have strong implications for battery management systems as they demonstrate that it is possible to use profiles generated with artificial intelligence to guide dynamic charging control, ensuring a better thermal stability of the battery and decreased ohmic losses without causing any additional short-term deterioration. Based on these insights, a holistic approach of combining generative optimization modules that can evaluate multiple charging trajectories in real time is recommended in the future, and in particular for applications as an EV using BMS. Additionally, there are benefits to industry adoption from the combination of generative AI with pack-level thermal management and safety constraints to ensure scalability. Future research efforts must be exerted in the areas of long-term experimental validation of artificially generated charging protocols, inclusion of cooling system models, investigation of diffusion-based generative architectures and application of the framework to various chemistries and aging conditions. Such advancements would add to the robustness, generizable, and real-world applicability of generative AI - driven fast-charging optimization.

References

- 1 Tomaszewska et al., "Lithium-ion battery fast charging: A review," ETransportation, vol. 1, p. 100011, 2019.

- 2 D. Chen, W. Zhang, C. Zhang, B. Sun, L. Zhang, and X. Cong, "Data-driven rapid lifetime prediction method for lithium-ion batteries under diverse fast charging protocols," *Journal of Energy Storage*, vol. 74, p. 109285, 2023.
- 3 G. Ning and B. N. Popov, "Cycle life modeling of lithium-ion batteries," *Journal of The Electrochemical Society*, vol. 151, no. 10, pp. A1584–A1591, 2004.
- 4 H. Xiao et al., "Recent advances in fast-charging lithium-ion batteries: Mechanism, materials, and future opportunities," *Chemical Engineering Journal*, p. 159927, 2025.
- 5 K. A. Severson et al., "Data-driven prediction of battery cycle life before capacity degradation," *Nature Energy*, vol. 4, no. 5, pp. 383–391, 2019.
- 6 K. Maher, A. Boumaiza, and R. Amin, "Thermal management challenges in lithium-ion batteries: Understanding heat generation mechanisms," *Chemical Communications*, vol. 61, no. 18, pp. 3740–3743, 2025.
- 7 K. Yang, S. Wang, L. Zhou, C. Fernandez, and F. Blaabjerg, "A critical review of AI-based battery remaining useful life prediction for energy storage systems," *Batteries*, vol. 11, no. 10, p. 376, 2025.
- 8 L. Xu, S. Wang, L. Xi, Y. Li, and J. Gao, "A review of thermal management and heat transfer of lithium-ion batteries," *Energies*, vol. 17, no. 16, p. 3873, 2024.
- 9 M. Alkhedher et al., "Electrochemical and thermal modeling of lithium-ion batteries: A review of coupled approaches for improved thermal performance and safety lithium-ion batteries," *Journal of Energy Storage*, vol. 86, p. 111172, 2024.
- 10 M. Armand et al., "Lithium-ion batteries—Current state of the art and anticipated developments," *Journal of Power Sources*, vol. 479, p. 228708, 2020.
- 11 N. Wassiliadis et al., "Review of fast charging strategies for lithium-ion battery systems and their applicability for battery electric vehicles," *Journal of Energy Storage*, vol. 44, p. 103306, 2021.
- 12 Programmer3, "EV Battery Charging Dataset," Kaggle, 2025. [Online]. Available: <https://www.kaggle.com/datasets/programmer3/ev-battery-charging-dataset>
- 13 S. El Fallah et al., "Advanced state of charge estimation using deep neural network, gated recurrent unit, and long short-term memory models for lithium-ion batteries under aging and temperature conditions," *Applied Sciences*, vol. 14, no. 15, p. 6648, 2024.
- 14 T. Liu, S. Ge, X. G. Yang, and C. Y. Wang, "Effect of thermal environments on fast charging Li-ion batteries," *Journal of Power Sources*, vol. 511, p. 230466, 2021.
- 15 T. R. Tanim et al., "Enabling extreme fast-charging: Challenges at the cathode and mitigation strategies," *Advanced Energy Materials*, vol. 12, no. 46, p. 2202795, 2022.
- 16 X. G. Yang, G. Zhang, S. Ge, and C. Y. Wang, "Fast charging of lithium-ion batteries at all temperatures," *Proceedings of the National Academy of Sciences*, vol. 115, no. 28, pp. 7266–7271, 2018.
- 17 X. Li, C. Yang, and P. Dubey, "Thermal management in lithium-ion batteries: Latest advances and prospects," *Batteries*, vol. 11, no. 9, p. 335, 2025.
- 18 Y. M. Dai, Y. C. Ting, C. M. Chang, and C. T. Huang, "Thermal management analysis of fast-charging lithium-ion battery packs: Effects of cooling strategies," *Next Energy*, vol. 9, p. 100465, 2025.
- 19 Y. Ortiz, P. Arévalo, D. Peña, and F. Jurado, "Recent advances in thermal management strategies for lithium-ion batteries: A comprehensive review," *Batteries*, vol. 10, no. 3, p. 83, 2024.
- 20 Y. X. Yao, L. Xu, C. Yan, and Q. Zhang, "Principles and trends in extreme fast charging lithium-ion batteries," *EES Batteries*, vol. 1, no. 1, pp. 9–22, 2025.
- 21 Z. Lin, D. Li, and Y. Zou, "Energy efficiency of lithium-ion batteries: Influential factors and long-term degradation," *Journal of Energy Storage*, vol. 74, p. 109386, 2023.