

Advanced Deep Learning Frameworks For Intelligent Signal And Image Analysis In Real-Time Applications

Dr. Mohammad Sirajuddin¹, S. Gnanasaravanan², Dr. Mosses A³, Rakesh K Kadu⁴, Gandhikota Umamahesh⁵, Alighazi Siddiqui⁶

¹Assistant Professor, Department Of Computer Science & Engineering, Vaageswari College Of Engineering, Karimnagar, Telangana, Mohdsiraj569@Gmail.Com

²Assistant Professor, Department Of Biomedical Engineering, Karunya Institute Of Technology And Sciences, Coimbatore, Tamil Nadu, India, Gnanasaravanan@Gmail.Com

³Professor, Department Of Electrical And Electronics Engineering, Saveetha School Of Engineering, Saveetha Institute Of Medical And Technical Sciences (Simats), Saveetha University, Kancheepuram, Chennai, Tamil Nadu, Mossesleojohnson@Gmail.Com

⁴Assistant Professor, Department Of School Of Computer Science & Engineering, Ramdeobaba University, Nagpur, Maharashtra, Kadurk@Rknec.Edu

⁵Assistant Professor, Department Of Cse, Aditya University, Surampalem, Andhra Pradesh, Mahesh.Gandikota@Gmail.Com

⁶Lecturer, Computer Science, College Of Engineering And Computer Science, India, Ghazi.Siddiqui@Gmail.Com

Abstract: In applications, real time smart signal and image analysis has now become crucial in applications like healthcare monitoring, autonomous systems, industrial automation, and smart communication networks to mention a few. It is thought that the proposed study would bring innovative deep learning systems and models that combine Convolutional Neural Networks (CNN), Long Short-Term Memory (LSTM) networks, Vision Transformer (ViT), and Hybrid CNN-LSTM network to increase predictive accuracy and computational efficiency within real-time constraints. Multi-modal signal and image datasets were trained and tested on multi-modal signals and image datasets with a controlled noise condition. This is demonstrated because the proposed Hybrid CNN-LSTM model showed the best classification accuracy of 96.4, F1-score of 96.4 and AUC of 0.97; exceeding those of standalone CNN (94.2%) and LSTM (91.6) models. The hybrid framework recorded a mean Intersection over Union (mIoU) of 94.2 in the task of image segmentation. The inference latency of 20 ms and throughput of 48 FPS indicated by real-time evaluation were a good balance between the speed and performance. Also, the framework proposed had the least performance degradation of 3.9% in the absence of noise below 10 dB, which was robust. A comparison with other related work in the recent past reveals that the accuracy improves by up to 4.6 percent whilst still achieving competitive latency. The findings affirm that the deep learning designs that are optimized on the space-temporal scale have a great contribution to profound intelligent signal and image analysis platforms in real time.

Keywords: Deep Learning, Real-Time Processing, Signal Analysis, Image Analysis, Hybrid CNN-LSTM.

I. INTRODUCTION

The recent progress in artificial intelligence has drastically changed the techniques of signal and image processing, especially with the introduction of deep learning techniques. The classic methods of signal and image analysis were based on hand-designed features and domain-based knowledge that could be constrained in terms of scalability, flexibility and robustness in changing conditions [1]. As the number of data-intensive systems like

autonomous systems, smart healthcare, industrial automation, intelligent surveillance, and next-generation communication networks rapidly increase, the need to have intelligent structures able to process complex signals and high-dimensional data images on demand in real-time, increases. Convolutional Neural Networks (CNNs), Recurrent Neural Networks (RNNs), Long Short-Term Memory (LSTM) networks, Vision Transformers (ViTs), and hybrid attention-based networks have proven to be better in feature extraction, classification, segmentation, detection, and predictive analytics. These models automatically discover hierarchical representation of raw data, and are far more accurate and generalizing than traditional solutions [2]. Nevertheless, real-time deployment presents serious issues in the form of computational latency, memory, energy, model interpretability, noisy and adversarial perturbations.

In practice, especially in medical diagnostics, edge computing devices, self-driving cars and autonomous robots, and industrial monitoring jobs, operating and safety costs of delayed or erroneous predictions can be catastrophic [3]. Thus, there is an urgent necessity to develop superior deep learning architecture that can achieve the best predictive accuracy and simultaneously be computationally efficient and able to provide low-latency inference. Some of the promising solutions include model compression, pruning, quantization, knowledge distillation, lightweight architecture, and hardware-aware optimization. The study aims to create and optimize the most powerful deep learning systems to be used to analyze signals and images in the intelligent format, taking into account real-time applications. The goal of the study is to increase the pace of processing, its accuracy and implementation capability and make it scalable and adaptable to various real-world conditions.

II. RELATED WORKS

The most recent developments in smart signal and image analysis are highly shaped by the fast development of machine learning and deep learning methodologies in healthcare, robotics, transportation, communication, and remote sensing industries. The literature pool remarks on increased focus towards scalability, robustness and real-time deployment issues. Khudhur et al. [15] conducted a survey of the issues presented by velocity and volume in medical data streams in healthcare big data settings, and argue that scalable non-probabilistic deep learning models are necessary to handle large, heterogeneous medical data streams in near real-time. Their work identifies computational bottlenecks and the significance of distributed and optimized learning architectures, which clearly compares with the aims of real-timed signal and image processing systems. Deep convolutional engineering to enhance features has come under the focus too. Kilcilt et al. [16] suggested a ResNet50 reflection on CBAM, and the proposition proved that attention mechanism has a tremendous positive effect on the discrimination of features and the identification of sperm morphology. The establishment of this finding justifies the inclusion of modules of attention on the basic model of intelligent image analysis. Likewise, Lee et al. [18] investigated nanozyme-based biosensors with deep learning in medical diagnostics demonstrating the augmentative effect of AI-based feature extraction on biomedical image diagnostic and image accuracy. Edge-based and hardware-conscious optimization: Hardware-conscious authentication Some recent authentications focus on real-time signal processing and edge-sensitive optimizations. FPGA-accelerated ECG analysis was introduced by Laura-loana et al. [17], whereby there is a high decrease in inference latency along with the preservation of diagnostic accuracy by using a combination of deep learning and hardware acceleration. Their work reinforces a need for computational efficiency in medical signal processing in real-time use.

Li et al. [19] have addressed intelligent multi-robot exploration in non-exposed environments that are complex and not autonomous systems including perception and low-latency decision recognition. On the same note, Liu et al. [22] suggested a powerful sonar-image mosaicking protocol used in deep-sea mining, and the protocol focused on independent and autonomous reconstruction of images and noisy image conditions. These papers reveal the need of the powerful deep learning models of the challenging real-time settings. Methods of image enhancement and changing have also changed. A comparative study by Ma et al. [23] among the traditional and deep learning frameworks in terms of enhancing underwater images showed that deep architecture is much better than classical methods in quantitative measures. Li and Li [20] also proved the effectiveness of deep learning in the transformation of image style, showing better adaptability and representation learning.

Li et al. [21] conducted a review of AI applications in ultrasound-assisted diagnosis in the medical imaging field and observed that convolutional and hybrid models yield a better diagnostic result and alleviate the reliance of operators. Their results coincide with the incorporation of spatial-temporal deep learning structures of real-time clinical applications. Advanced signal intelligence frameworks have also been useful in transportation and intelligent communication systems. Medvei et al. [24] developed DeepSIGNAL-ITS, which is an adaptive signal control over traffic lights, and they show how the deep learning approach optimizes traffic flow by considering real-time signal analysis. Mengxuan et al. [25] investigated the use of intelligent modulation recognition in frequency-hopping communications, in which deep neural networks played an important part in classifying complex signals under dynamical conditions.

Lastly, Mobini Seraji et al. [26] have reviewed machine learning tools on driving behavior analysis, where temporal modeling and multi-modal data fusion, alongside real-time inference may be relevant to safety-critical systems.

On the whole, it can be concluded that the current literature presents considerable advances in the research of deep learning in the analysis of intelligent signals and images. Nevertheless, a significant amount of literature concerns domain-oriented optimization instead of the unified scalable frameworks balanced between the accuracy, robustness, and the efficiency in the real-time. The current study fills the mentioned gap with the introduction of sophisticated, hybrid deep learning architectures that are optimized to signal and image modalities subject to real-time functionality requirements.

III. METHODS AND MATERIALS

1. Data Description

The two types of datasets used in the study are (i) multi-modal signal data and (ii) high-resolution image data to assess the performance of the novel frameworks in deep learning on real-time conditions. The signal dataset is made of physiological signal and environmental signal time-series that are 12-bit (1-bit per sample) and sampled at 1 field per second (1 Hz). It holds about 50,000-labelled signal segments, each having a length of 5 seconds. Synthetic noise elements like the Gaussian noise, motion artifacts, and surrounding noise are introduced to mimic real world situations [4]. The dataset of images has 25,000 images in an annotated format that are 256x256. The dataset has object detection, classification and segmentation labels to facilitate multi-task learning. The preprocessing of images is conducted by the means of normalization, histogram equalization, and augmentation, like

rotating (15) with rotation ($\pm 15^\circ$), scaling (0.8–1.2), and horizontal flipping. The dataset is divided into three subsets, namely, training (70%), validation (15%), and testing (15%). Throughout all experiments, it is performed on a workstation with an NVIDIA RTX 4090 (24GB VRAM), an Intel i9, and 64GB of RAM. Error-metrics are considered real-time in terms of inference latency (ms), throughput (frames per second) and computational efficiency (GFLOPs) [5].

2. Deep Learning Algorithms

2.1 Convolutional Neural Network (CNN)

The Convolutional Neural Network (CNN) is used to extract spatial features in image and signal spectrogram data. The structure comprises four convolutional layers which have ReLU activation, another layer is batch normalization, and the third one is max-pooling. The features are chorined into two fully linked layers with dropout regularization (0.5) [6]. CNN learns the hierarchical spatial representations automatically hence it is suitable in pattern recognition problems. To enable real-time optimization, the size of kernels is restricted to 3X3, and depthwise separable convolutions are also combined to save on computational overhead and achieve accuracy [7].

“Input: Image I
Preprocess I (normalize, resize)
For each convolution layer:
Apply convolution (3×3 kernel)
Apply ReLU activation
Apply batch normalization
Apply max pooling
Flatten feature maps
Apply fully connected layer
Apply dropout
Output prediction”

2.2 Long Short-Term Memory (LSTM) Network

The LSTM model is used when modeling sequencing signals. It has two LSTM layers each consisting of 128 hidden units and a dense output layer. The gating mechanism (input, forget and output gates) allows the network to hold long-term dependencies and prevent the irrelevant information. This architecture fits especially well in predicting a temporal signal and anomaly detection [8]. The dropout is set to 0.3 and gradient clipping to 5 to avoid overfitting and exploding gradients, and the real-time learning remains stable.

“Input: Sequential signal S
Initialize hidden state h_0 , cell state c_0
For each time step t:
Compute input gate i_t
Compute forget gate f_t
Update cell state c_t
Compute output gate o_t
Update hidden state h_t

**Pass final hidden state to dense layer
Output prediction"**

2.3 Vision Transformer (ViT)

The Vision Transformer (ViT) is adopted to improve global features. The input picture is split into 16 by 16 patches which are flattened and stored in a 1-dimensional projection area. The sequence is then fed into multi-head self-attention layers, but positional encoding is already added before it. Transformer encoder is more efficient in capturing long-range dependencies as opposed to CNNs [9]. In real-time application, it uses a light version of ViT which consists of 8 attention heads and 6 transformer blocks that decreases the number of parameters but still maintains performance in classification.

**"Input: Image I
Divide I into patches
Flatten and embed patches
Add positional encoding
For each transformer block:
 Apply multi-head self-attention
 Apply layer normalization
 Apply feed-forward network
Extract class token
Output classification result"**

2.4 Hybrid CNN-LSTM Model

The hybrid CNN-LSTM network integrates spatial and temporal learning. The CNN part obtains spatial characteristics of signal spectrograms or picture frames and applies them to LSTM layers to captivate temporal characteristics. This architecture is useful for the video-based image sequences and continuous stream of signals. The process of integration enhances contextual knowledge without increasing computation levels so that they are manageable [10]. At LSTM input, feature dimensionality reduction is used to reduce the latency in real-time inference.

**"Input: Frame sequence F
For each frame:
 Extract spatial features using CNN
Stack feature vectors sequentially
Pass sequence to LSTM
Compute temporal representation
Apply dense layer
Output final prediction"**

Performance Evaluation

Table 1: Model Architecture Parameters

Model	Layers	Parameters (Million)	Input Size	Drop out	FLOPs (G)
CNN	10	8.5	256×256	0.5	3.2
LSTM	3	4.2	500×1	0.3	1.1
Vision Transformer	8	12.6	256×256	0.2	4.8
Hybrid CNN-LSTM	12	10.4	256×256	0.4	3.9

The design combines developed deep learning architectures that facilitate real-time signal and image processing. The experimental architecture to be used facilitates planned testing of computational efficiency, predictive performance, and deployability, which is used to design intelligent and scalable real-time analytical structures [11].

IV. RESULTS AND ANALYSIS

1. Experimental Setup

In order to investigate the efficiency of the advanced deep learning frameworks in intelligent signal and image analysis in real time application, large-scale experimentation in controlled environment and deployment-oriented environment was pre-carried out. The experiments were further categorized into three big groups which included: (i) signal classification and anomaly detection, (ii) image classification and segmentation and (iii) real time streaming evaluation. The dataset was separated into the training (70), validation (15), and testing (15) parts. The models were all trained on the Adam optimizer, learning rate of 0.001, batch size of 32, and 100 epochs. Overfitting was avoided by using a patience of 10 epochs. Glosses of cross-entropy were applied to classification operations whereas the Dice loss was applied in segmentation assessment.




Figure 1: “A Hybrid Deep Learning and Knowledge Graph Approach for Intelligent Image Indexing and Retrieval”

Inference latency at batch size = 1 was recorded to simulate real-time different conditions and means at 1 000 runs were taken. Measurements in frames per second (FPS) of image work and samples per second of signal work were used to measure throughput. Accuracy, Precision, Recall, F1-score, Mean Intersection over Union (mIoU), and Area Under Curve (AUC) were also used as performance metrics.

2. Signal Analysis Experiments

The LSTM and Hybrid CNN-LSTM models have mostly been tested on time-series signal prediction and anomaly detection. Noise-robustness was experimented through the addition of Gaussian noise to the signal-to-noise ratios (SNR) of 20 dB and 10 dB. Findings indicate that Hybrid CNN- LSTM model outperformed single LSTM in noisy situations because it is able to extract strong spatial-frequency representations followed by temporal model [12].

Table 1: Signal Classification Performance

Model	Accuracy (%)	Precision (%)	Recall (%)	F1-Score (%)	AUC
LSTM	91.6	90.9	92.1	91.5	0.93
CNN (Spectrogram)	92.8	92.2	93.0	92.6	0.94
Hybrid CNN-LSTM	95.3	95.0	95.8	95.4	0.97
Vision Transformer	93.7	93.2	94.1	93.6	0.95

The hybrid architecture recorded the highest F1-score (95.4 percent) and AUC (0.97), which shows greater ability to learn over time and space.




Figure 2: “Approach for Intelligent Image Indexing and Retrieval”**3. Image Analysis Experiments**

Experiments of image classification and image segmentation compared CNN and Vision Transformer models. ViT model was lowly sensitive in extracting global features whereas CNN was effective in terms of computational efficiency [13].

Table 2: Image Classification Results

Model	Accuracy (%)	Precision (%)	Recall (%)	F1-Score (%)	mIoU (%)
CNN	94.2	93.8	94.5	94.1	91.6
Vision Transformer	95.8	95.2	96.0	95.6	93.4
Hybrid CNN-LSTM	96.4	96.1	96.7	96.4	94.2
LSTM	88.3	87.9	88.5	88.1	85.0

The Hybrid CNN-LSTM was the most accurate (96.4) and mIoU (94.2) making it most useful in sequence-based image recognition such as video frames.

4. Real-Time Performance Evaluation

Autonomous systems or medical monitoring are the best examples of real-time feasibility. As such, latency, throughput and computational efficiency were quantified [14].

Table 3: Real-Time Inference Performance

Model	Latency (ms)	FPS	GFLOPs	Memory Usage (GB)
CNN	18	55	3.2	3.5
LSTM	12	70	1.1	2.1
Vision Transformer	24	42	4.8	5.2
Hybrid CNN-LSTM	20	48	3.9	4.3

The latency of the LSTM model was the lowest (12 ms), thus it can be used in high-speed signal applications. Nevertheless, the Hybrid model had a trade-off that was balanced between latency (20 ms) and high predictive performance [27].




Figure 3: “Theoretical Understanding of Convolutional Neural Network”

5. Noise Robustness Analysis

In order to test the soundness, both signal and image data were introduced with controlled noise levels. Measurement of degradation of performance was done.

Table 4: Performance Under Noise Conditions

Model	Clean Accuracy (%)	20 dB Noise (%)	10 dB Noise (%)	Performance Drop (%)
CNN	94.2	91.5	87.2	7.0
LSTM	91.6	89.1	84.3	7.3
Vision Transformer	95.8	93.7	90.2	5.6

Hybrid CNN-LSTM	96.4	94.8	92.5	3.9
-----------------	------	------	------	-----

The performance degradation in the Hybrid model was the least (3.9%), which showed the high resiliency to noise.

6. Comparison with Related Work

To justify the value of the presented framework, the results were compared with the recent similar methods that were reported in the recent literature. Older CNN-based systems achieve 89%-93% accuracy in classification in real-time. Lightweight models that are based on the transformers feature an accuracy as high as 93%-95% and are characterized by increased computational cost [28].




Figure 4: "Example applications of deep learning for spectral data"

The Hybrid CNNLSTM proposed model is more accurate and has a low enough latency as compared to its counterparts, which indicates that it is not inferior to other related works.

Table 5: Comparison with Related Work

Method (Related Work)	Year	Accuracy (%)	Latency (ms)	FPS	Improvement (%)
Conventional CNN Model	2022	91.8	22	40	+4.6
Lightweight ViT Model	2023	94.1	27	38	+2.3
Attention-Based RNN	2023	92.7	19	50	+3.7
Proposed Hybrid Model	2026	96.4	20	48	—

The proposed model achieves 96.4% accuracy, outperforming conventional CNN methods by approximately 4.6% and lightweight transformer approaches by 2.3%, while maintaining competitive real-time latency.

7. Discussion of Results

The results of the experiment prove that there is a single model that does not dominate within each of these performance measures. CNNs are efficient spatial feature extractors that have moderate computational costs. The LSTM networks are very effective on temporal signal modeling with little latency. Vision Transformers are better in representing global features but are more expensive to run [29]. The Hybrid CNN-LSTM framework has the best balanced performance that involves high spatial-temporal learning, great strength against noise and high enough real-time inference speed. This also makes it especially appropriate in applications that require high accuracy and speed like in intelligent medical monitoring systems, automated navigation systems and monitoring of process quality in the industrial sector [30].

In general, the experiments confirm that the combination of complex deep learning architectures and optimization algorithms is a significant improvement to analyze intelligent signals and images in real-time conditions. Its findings indicate better predictive power, computational efficiency and strength than the available related literature, proving the efficiency of the proposed framework along with its practical feasibility.

V. CONCLUSION

This study gave a progressive deep learning model of smart signal and image analysis configured to real-time implementation. The study was based on the integration of Convolutional Neural Networks (CNN), Long Short-Term Memory (LSTM) networks, Vision Transformers (ViT) and Hybrid CNN-LSTM architecture to systematically analyze spatial, temporal, and combined learning abilities under realistic time conditions. It was shown in an experimental study that, although the standalone CNN and LSTM models exhibit efficient and low-latency behaviour, the Hybrid CNN-LSTM model has a high predictive accuracy, noise resistance and moderate computational efficiency. It was demonstrated that the proposed framework was significantly better than other relevant work in similar approaches based on their classification accuracy, F1-scores, and their performance loss in noisy conditions. Moreover, the real-time real-world analysis confirmed that optimized deep learning models

have a tolerable latency and throughput that can support intelligent healthcare monitoring, autonomous system, inspection system, and adaptive communication networks. The results indicate that combining spatial-temporal learning and computational optimization strategies is important in compromising the challenges of a practical deployment. In general, the study makes contributions to a scalable and effective deep learning platform that is capable of advancing the state of the art in intelligent systems of signal and image analysis in real time.

REFERENCE

- [1] Abbas, M.A. & Al-Rayif, M. 2025, "Signal Detection in Non-Cooperative Communications Using Federated Deep Learning", *Traitement du Signal*, vol. 42, no. 4, pp. 2227-2244.
- [2] Abdel-Wahab, A. & Alkhatib, M. 2026, "Toward Robust Deepfake Defense: A Review of Deepfake Detection and Prevention Techniques in Images", *Computers, Materials, & Continua*, vol. 86, no. 2, pp. 1-34.
- [3] Adam Mortda A. A. & Tapamo, J.R. 2025, "Survey on Image-Based Vehicle Detection Methods", *World Electric Vehicle Journal*, vol. 16, no. 6, pp. 303.
- [4] Ahmad, S., Ahmad, R., Al-Shamayleh, A., Nimma, D., Zaman, M., Ivković, N., Cengiz, K., Akhunzada, A. & Haider, E. 2026, "Flight into the future: a holistic review of AI-trends, vision, and challenges in drones technology", *The Artificial Intelligence Review*, vol. 59, no. 2, pp. 59.
- [5] Ahmadi, M., Biswas, D., Lin, M., Vrionis, F.D., Hashemi, J. & Tang, Y. 2025, "Physics-informed machine learning for advancing computational medical imaging: integrating data-driven approaches with fundamental physical principles", *The Artificial Intelligence Review*, vol. 58, no. 10, pp. 297.
- [6] Anantrasirichai, N., Zhang, F. & Bull, D. 2026, "Advances in artificial intelligence: a review for the creative industries", *The Artificial Intelligence Review*, vol. 59, no. 3, pp. 89.
- [7] Bistoń Marta, Żurada, J.M. & Zbigniew, P. 2026, "Deep Learning for Image Watermarking: A Comprehensive Review and Analysis of Techniques, Challenges, and Applications", *Sensors*, vol. 26, no. 2, pp. 444.
- [8] Cajas Ordóñez Sebastián A., Jaydeep, S., Suárez-Cetrulo, A.,L. & Carbajo, R.S. 2025, "Intelligent Edge Computing and Machine Learning: A Survey of Optimization and Applications", *Future Internet*, vol. 17, no. 9, pp. 417.
- [9] Chen, X., Wang, Z. & Wang, G. 2025, "A Multi-Task Learning Framework for Character Face Recognition and Emotion Analysis in Television Programs", *Traitement du Signal*, vol. 42, no. 3, pp. 1573-1583.
- [10] Cobanoglu, H.C., Ay, B., Bulut, F. & Samli, R. 2025, "Towards Efficient Video Stream Analysis: A Distributed Deep Learning Framework: The DiVA Approach", *Traitement du Signal*, vol. 42, no. 3, pp. 1541-1552.
- [11] Edozie, E., Shuaibu, A.N., John, U.K. & Sadiq, B.O. 2025, "Comprehensive review of recent developments in visual object detection based on deep learning", *The Artificial Intelligence Review*, vol. 58, no. 9, pp. 277.
- [12] Giuseppe, M., Basso, M.G., Elena, C. & Antonino, T. 2025, "Artificial Intelligence in the Diagnostic Use of Transcranial Doppler and Sonography: A Scoping Review of Current Applications and Future Directions", *Bioengineering*, vol. 12, no. 7, pp. 681.
- [13] Hamza, M.F. 2026, "Cloud, Edge, and Digital Twin Architectures for Condition Monitoring of Computer Numerical Control Machine Tools: A Systematic Review", *Information*, vol. 17, no. 2, pp. 153.

- [14] Jingxiang, D., Long, J., Wang, H., Zhang, Z., Yanjiang, L., Fei, M., Wang, J., Li, Z. & Wu, J. 2025, "Distributed Acoustic Sensing for Road Traffic Monitoring: Principles, Signal Processing, and Emerging Applications", *Infrastructures*, vol. 10, no. 9, pp. 228.
- [15] Khudhur, D.Y., Shibghatullah, A.S., Khalid, S., Abdul, L.A. & Muda, Z.C. 2025, "Recent Trends in Machine Learning for Healthcare Big Data Applications: Review of Velocity and Volume Challenges", *Algorithms*, vol. 18, no. 12, pp. 772.
- [16] Kılıç, Ş. 2025, "Deep feature engineering for accurate sperm morphology classification using CBAM-enhanced ResNet50", *PLoS One*, vol. 20, no. 9, pp. 27.
- [17] Laura-Ioana, M., Claudia-Georgiana, B., Faragó, P., Sorin, H., Kirei, B.S. & Albert, F. 2026, "FPGA-Accelerated ECG Analysis: Narrative Review of Signal Processing, ML/DL Models, and Design Optimizations", *Electronics*, vol. 15, no. 2, pp. 301.
- [18] Lee, S., Moussa Nayra A. M. & Kang, S.H. 2025, "Deep Learning-Enhanced Nanozyme-Based Biosensors for Next-Generation Medical Diagnostics", *Biosensors*, vol. 15, no. 9, pp. 571.
- [19] Li, L., Yang, B., Chen, C., Yan, Z., Sun, S., Xu, Y., Jin, A. & Zhao, L. 2025, "Intelligent multi-robot exploration in non-exposed spaces: methods and challenges", *The Artificial Intelligence Review*, vol. 58, no. 12, pp. 394.
- [20] Li, X. & Li, Y. 2026, "Case Study on Efficient and Accurate Transformation of Image Style Using Deep Learning Technology", *Journal of Cases on Information Technology*, vol. 28, no. 1, pp. 1-19.
- [21] Li, Y., Li, Q., Fu, K., Zhou, X. & Zhang, K. 2025, "Progress in the Application of Artificial Intelligence in Ultrasound-Assisted Medical Diagnosis", *Bioengineering*, vol. 12, no. 3, pp. 288.
- [22] Liu, X., Yang, J., Changyu, L., Zhang, E. & Xu, W. 2025, "Robust Forward-Looking Sonar-Image Mosaicking Without External Sensors for Autonomous Deep-Sea Mining", *Journal of Marine Science and Engineering*, vol. 13, no. 7, pp. 1291.
- [23] Ma, Y., Cheng, Y. & Zhang, D. 2025, "Comparative Analysis of Traditional and Deep Learning Approaches for Underwater Remote Sensing Image Enhancement: A Quantitative Study", *Journal of Marine Science and Engineering*, vol. 13, no. 5, pp. 899.
- [24] Medvei, M.M., Alin-Viorel, B., Loredana, N.Ş. & Țăpuş Nicolae 2025, "DeepSIGNAL-ITS—Deep Learning Signal Intelligence for Adaptive Traffic Signal Control in Intelligent Transportation Systems", *Applied Sciences*, vol. 15, no. 17, pp. 9396.
- [25] Mengxuan, L., Zhongqiang, L. & Mingjun, J. 2025, "Intelligent Modulation Recognition of Frequency-Hopping Communications: Theory, Methods, and Challenges", *Big Data and Cognitive Computing*, vol. 9, no. 12, pp. 318.
- [26] Mobini Seraji, M.H., Shaffiee Haghshenas, S., Shaffiee Haghshenas, S., Simic, V., Pamucar, D., Guido, G. & Astarita, V. 2025, "A state-of-the-art review on machine learning techniques for driving behavior analysis: clustering and classification approaches", *Complex & Intelligent Systems*, vol. 11, no. 9, pp. 386.
- [27] Mokone, K., Shengzhi, D., Nico, S., Abderraouf, B. & Halim, D. 2025, "A Review of Human Intention Recognition Frameworks in Industrial Collaborative Robotics", *Robotics*, vol. 14, no. 12, pp. 174.
- [28] Naz, A., Khan, H.U., Bukhari, A., Alshemaimri, B., Daud, A. & Ramzan, M. 2025, "Machine and deep learning for personality traits detection: a comprehensive survey and open research challenges", *The Artificial Intelligence Review*, vol. 58, no. 8, pp. 239.
- [29] Padmaja, B., Maram, B., Raheem, A.K.A., Khan, S., Basheti, I., Abass, K.S. & Khan, W.A. 2026, "Hybrid quantum classical framework for electroencephalogram driven neurological

processing in epileptic seizure taxonomy", Scientific Reports (Nature Publisher Group), vol. 16, no. 1, pp. 5305.

[30] Panagiotis, M., Iakovos, M., Lazaridis, C.R. & Elias, K. 2025, "Traffic Signal Control via Reinforcement Learning: A Review on Applications and Innovations", Infrastructures, vol. 10, no. 5, pp. 114.