

Non-Destructive Prediction Of Sperm Dna Fragmentation Using Deep Learning: A Comprehensive Review Of Clinical, Computational, And Federated Approaches

Mr. Pankaj S. Umate¹, Dr. Kailash D. Kharat², Dr. Vikul J. Pawar³

¹PhD Research Scholar, CSE Government College of Engineering, Aurangabad, Chh. Sambhajinagar

²Associate Professor CSMSS Chhatrapati Shahu College of Engineering, Chh. Sambhajinagar

³Assistant professor, CSE Government College of Engineering, Aurangabad, Chh. Sambhajinagar

Abstract— Male infertility is most common cause in reproductive failure worldwide. Still, routine clinical procedures relies largely on conventional semen analysis standardized by the World Health Organization (WHO), which is less accurate to provide details regarding molecular integrity of sperm DNA [2]. In recent years, sperm DNA fragmentation (SDF) has evolved as a measurable indicator for impaired fertilization, compromised embryo development, recurrent pregnancy loss, and less success rates in assisted reproductive technologies [18]. However, laboratory techniques for assessing SDF – such as TUNEL, SCSA and Comet assay - are destructive in nature and difficult to apply consistently through diverse clinical settings.

This review gives a detailed and clinically grounded overview for deep learning approaches for non-destructive SDF prediction using sperm microscopy images. Evolution of neural networks and distributed learning systems provide advancement in medical imaging [10]. We analyse the advancement of convolutional neural networks (CNNs) and transformer-based architectures in biomedical image analysis including AI-assisted sperm assessment.

This review dives deeper into multi-task learning strategies that jointly model related sperm characteristics, as well as attention-based multiple-instance learning techniques that enable reliable sample-level predictions from collections of individual cell images. To handle variability across laboratories and imaging platforms, we study domain generalization and adaptation methods along with self-supervised and in-silico labelling approaches that enhance data efficiency.

Federated learning model approaches are adopted for the development of AI systems in fertility clinics in a decentralized manner. This research aims to build upon the current body of knowledge in the areas of harmonization, the application of double-blind annotation approaches, the resolution of reproducibility problems associated with morphological grading, dealing with the variability of different domains, and the identification of potential biases in medical image datasets. Calibration approaches and interpretability techniques, including gradient-based saliency techniques and feature-based techniques such as Grad-CAM and SHAP, are identified as critical components in the development of trustworthy AI systems.

Previous research has shown that multi-task and federated deep learning models have better performance than traditional single-task models in terms of morphology assessment and SDF prediction, and that they have robust performance in adverse imaging conditions and across different domains.

Through the integration of clinical reproductive diagnostics with scalable and privacy-conscious frameworks of neural learning, AI-assisted computer-assisted systems demonstrate significant promise for facilitating objective, reproducible, and clinically viable fertility assessments. The analysis presented here identifies existing unsolved bottlenecks related to annotated data availability, domain adaptation challenges, clinical validation requirements, and regulatory readiness while outlining future research directions related to the interplay of medical imaging, distributed optimization, and trustworthy AI. Together, these developments highlights the increasing potential of non-destructive SDF prediction as a transformative application of next-generation learning systems in precision reproductive medicine.

Index Terms— Artificial intelligence, Assisted reproductive technology (ART), Clinical decision support systems, Convolutional neural networks (CNN), Deep learning, Domain generalization, Federated learning, Image segmentation, Male infertility, multi-task

learning, Quantitative phase imaging (QPI), Sperm DNA fragmentation (SDF), Sperm morphology analysis, YOLO object detection

1. INTRODUCTION

Infertility is a rising social health issue which plagues almost every sixth couple of reproductive age worldwide. Of them, male factors are the cause of nearly half of infertility but behind the scenes, the reasons are very likely to be untouched or misdiagnosed. Despite advances in reproductive medicine, the evaluation of the male fertility continues to depend mostly on traditional semen standardized parameters of analysis, i.e. concentration, motility and morphology, introduced by the World.

Laboratory Manual of the Examination and Processing of Human by the Health Organization (WHO) Semen. These tests though helpful give a shallow picture of sperm quality and tend to be in most cases unreliable do not detect molecular anomalies that have a crucial effect on fertilization success.

Conventional semen analysis is descriptive and much operator-biased. Even with WHO 2021 protocols, lab technique, subjective. Considerable diagnostic variability is caused by interpretation, inter-observer inconsistencies. Moreover, standard parameters such as motility or morphology are in no way always correlated with. The success rates or results of pregnancy in assisted reproductive technologies (ART) like in vitro. IVF and intracytoplasmic sperm injection (ICSI). Therefore, clinicians tend to be deficient the molecular pathways to comprehensively assess male reproductive potential.

On the quality level of sperm, a more profound approach is required than microscopic analysis. Sperm DN fragmentation is one of the most serious molecular determinants of male fertility (SDF) - a sperm genome measure of integrity. Improved standards of DNA fragmentation.

Mitochondrial abnormalities in the sperm cells have been associated severally with infertility, defective embryonic growth, early miscarriage, and lower birth rates of live births especially in ART procedures. Hence, SDF has emerged as a key predictive biomarker of assessing the potential of male fertility outside conventional parameters.

SDF is an indication of numerous underlying processes, such as oxidative stress [16], varicocele, old age, infections, environmental poisons, and maladjusted chromatin wrappings. High levels of SDF signify single and double strand DNA breaks that may damage fertilization, invalidate viability of embryos, and endanger the genetic abnormality of the offspring. Clinically, SDF testing is a better indicator of sperm health; it has however not been widely adopted because of the complicatedness and intrusiveness of existing lab tests [17], [20].

The current methods of measuring SDF using the gold-standard, including the TUNEL assay [6], Sperm Chromatin Structure Assay (SCSA) [7], and Comet assay [8] - each has its merits and limitations. TUNEL assay [6], a technique of DNA strand break detection, is an example technique that labels the strand breaks with fluorescent markers. SCSA estimates the using the acridine orange staining and flow cytometry. Although the Comet assay [8] uses single-cell electrophoresis to visualize the quantity of DNA fragments, DNA fragmentation index (DFI), can be used instead imagine fragmenting DNA in the form of comet-shaped tails with the use of fluorescence microscopy. Although these tests are precise, they are time consuming, technical and harmful to sperms samples, so that they are not reused in reproductive procedures.

Moreover, these assays differ in the reproducibility and scalability. SCSA is standardized and can be analyzed in large scale but instrumentation is costly. The TUNEL assay [6] is labor-intensive and cell-specific. The Comet assay [8] is highly sensitive, however, and is sensitive to operator technique as well as the conditions of the electrophoresis. The SCD/HALO test is cheaper, but not as effective qualitative in nature. All the

aforementioned constraints have hindered the routine SDF testing carried out in the majority of the fertility clinics, especially in resource-limited settings [14].

Besides the aforementioned challenges, there has been a revolution in the technology used for clinical imaging. High-throughput imaging, along with digital microscopy, has completely changed the landscape of andrology laboratory diagnosis. Bright-field microscopy, phase-contrast microscopy, and fluorescence microscopy. Thousands of high-resolution sperm images can now be captured in minutes in systems and this has preserved them form and texture way beyond the human perception. These vast imaging datasets offer a unique possibility of computational modeling and artificial intelligence (AI) based interpretation [39].

Artificial intelligence (AI) and deep learning (DL) [9], [21] have become the disruptive technologies in the field of medical image analysis. In particular, convolutional neural networks (CNNs) [9], [22] have proven to be remarkably learning morphological and textual patterns direct out of raw images, to the exclusion of traditional custom-made feature-based methods. CNN-based models have been used in the field of reproductive biology. Effectively extended to sperm morphology classification, motility tracking and vitality estimation. Recently, deep learning has demonstrated the potential to predict the non-destructive prediction of the fragmentation of DNA with label-free modes of imaging. A number of research studies have investigated the prediction of SDF through AI in the framework of bright-field and fluorescence imaging data. In one method, stain-free quantitative-phase imaging was used together using machine learning algorithms the cell-level fragmentation was predicted with reasonable accuracy. The other study used the pretrained CNNs to generate the discriminative features of acridine-orange. Stained sperm images, with moderate correlations with DNA quality measured. This evidence indicates that AI is capable of identifying subtle optical signals linked to chromatin integrity, possibly doing away with the destructive assays.

In spite of these optimistic innovations, the discipline has a number of significant bottlenecks. One major limitation is the absence of large, annotated and standardized datasets that comprise conventional semen parameters whose SDF ground truth has been demonstrated. Biases in the dataset, changes in imaging equipment, staining regimes, and light regimes tend to shift domain scales that impede model's generalization. More than that, the majority of available research is based on limited, one-centre datasets, which is limiting clinical usability and interpopulation and interlaboratory reproducibility.

The other difficulty is the lack of standardized systems of harmonization of data and annotation. Clinical datasets are generally disjointed, and their metadata's are inconsistent, including age, period of abstinence, or imaging modality. Unless well standardized and marked, supervised cross-domain variability cannot be effectively captured and clinically cannot be achieved with learning models acceptable accuracy. That is why the basis of a well-functioning AI-based decision support system should be a comparatively strong, multi-source dataset containing annotations of sperm morphology, which are reliable, motility, and DNA integrity.

The proposed research will fill this gap by developing a better annotated dataset of sperm images which contains validated DNA fragmentation tags obtained in clinical databases and databases made publicly accessible. This detailed data shall be used as the infertility diagnosis clinical decision support system based on scalable and AI-assisted backbone.

The proposed framework integrates multiple key components:

- **Standardized curation and annotation of data** - adding pictures of various kinds' microscopy modalities and making metadata interoperable.
- **Multi-task learning models** - con-current prediction of traditional semen parameters (morphology, motility) and the levels of DNA fragmentation [37].

- **Federated learning architecture** - This allows joint training banquet halls without compromising data security.
- **Tools of explainability and interpretability** - through visual means of explanation such as Grad-CAM [26] or SHAP [27] to increase clinician trust and regulatory compliance.

With a combination of these aspects, the system will be targeted to provide an automated, non-destructive, and diagnostic tool, which can be obtained repeatedly and can be used to supplement the current clinical processes. The use of federated and privacy-preserving AI will guarantee scalability of institutions without endangering patient confidentiality. Real-world clinical is also facilitated through this decentralized model deployment, in which sensitive patient information is not able to be distributed outside of the company. Clinically, the proliferation of the AI-driven computer-assisted analysis would be capable of improve diagnostic basis and throughput dramatically. Automated sperm assessment eliminates subjectivity, includes minimal human error and offers measurable metrics that are correlated with reproductive outcomes. In addition, combining molecular-level understanding such as SDF prediction enables the more comprehensive analysis of male fertility, which results in more appropriate treatment decisions ART success rates.

Research wise, the establishment of an open, annotated dataset containing DNA the labels of fragmentation will hasten the advancement of reproductive AI. It will allow reproducibility, comparative studies between imaging modalities and algorithms, benchmarking, and comparative studies between different algorithms and imaging modalities. Over time, such datasets can be useful in generalizing foundation models that are able to generalize clinics and imaging technologies which were the main part of the next-generation clinical decision support systems (CDSS).

This shift in AI-based fertility diagnostics is morally correct in relation to the overall shift towards precision medicine. Using customer diagnostic models and clinical profiles, clinicians will be able to offer personalized counselling and specific intervention, cutting down on superfluous ART cycles and emotional sufferings to fertility couples treatment [40].

The diagnosis of infertility is set to undergo the change of the incorporation of artificial intelligence, high-level microscopy, and large-scale marked-up collections. The proposed AI-driven Computer Assisted System aims at filling in between the conventional semen examination and molecular diagnostics exploiting the deep learning methods based on harmonized and multi-centric datasets. The end goal to transform an enhanced annotated dataset of sperm images with verified DNA fragmentation labels is not only a problem in data engineering but also a problem.

Essential step on the way to scalable, explainable, and clinically relevant decision support systems in reproductive medicine.

Since this framework can be used as an outline of more general uses in reproductive biology, as oocyte and embryo testing, genetic risk testing and environmental fertility impact studies. This AI will improve clinical interpretability, automation, and standardization. The next generation-based system could redefine the diagnosis and management of male infertility and open the pathway to the era of data-driven reproductive healthcare.

2. LITERATURE REVIEW

The research in infertility has developed very fast in the recent decades, yet precise and repeatable evaluation of male fertility is a long-standing clinical issue. The basis of andrology diagnostics is conventional semen analysis carried out in accordance with the recommendations of the World Health Organization (WHO) [1] Laboratory Manual (6th Edition, 2021). The manual gives standard procedures of semen collection, processing

and reporting with the aim of reducing variations in laboratories. Nevertheless, even these strict guidelines cannot be met in reality, as there is usually no real standardization. The lack of consistency in staining procedures, inconsistency in microscope optics, inconsistency in sample handling, and microscopy variability by operator still negatively affect reproducibility. As a result, the inter-laboratory consistency of morphology grading, motility analysis and inter-laboratory comparison has been one of the greatest challenges in male fertility studies and in clinical diagnostics.

WHO 6th edition [1] refined a few methodological improvements, and practices are currently in line with ISO 23162: 2021 semen examination. They are the updated motility categories, better quality control guidelines, and the orientation on harmonized data reporting. Nevertheless, the most difficult parameter for sperm morphology is still held captive by the subjectivity of interpretation. The application of morphological analysis according to the strict criteria of Kruger has always been considered an indicator of the fertilization potential of sperm cells, although its usefulness has often been the subject of discussion. The discrepancy is an indication of the need for an objective, reproducible, and potentially automatable technique for the measurement of sperm morphology [15].

The introduction of sperm DNA fragmentation (SDF) [3], [4], [5] in place of diagnosis has essentially widened the diagnostic horizon. SDF offers predictive capability beyond any traditional parameters as it offers molecular level understanding of the genomic integrity of a sperm. There is a strong association between high DNA Fragmentation Index (DFI) and subfertility, recurrent pregnancy loss, and low embryo development in assisted reproductive technologies (ART). Meta-analyses always point out that high levels of DFI are associated with reduced rates of natural conception, increased risk of miscarriage and reduced ART success. So, SDF testing is becoming a required precaution in clinical judgment in cases of unexplained infertility, recurrent pregnancy loss, and recurrent ART failure [19].

❖ ***Sperm DNA Fragmentation (SDF) Assays and Their Limitations***

The SDF testing sector is dominated by three principal families of assays: the TUNEL assay [6], the Sperm Chromatin Structure Assay (SCSA(r)) and the Comet assay [8]. Both are associated with their methodological advantages and disadvantages.

The TUNEL assay [6] (Terminal deoxynucleotidyl transferase dUTP nick end labeling) uses the presence of free 3'-OH ends of DNA strands as a sign of strand breakages by tagging them with fluorescent substances. It can be utilized at the single-cell resolution, which is why it is perfect to study the heterogeneity of sperms in detail. Nevertheless, the test is the most destructive, time consuming, and also needs expertise in flow cytometry or fluorescence microscopy. Its protocols are not standardized universally and therefore are varied among the laboratories. ACO staining and flow cytometry are used in the SCSA to measure the level of DNA susceptibility to acid-induced denaturation. It gives two indices the DNA Fragmentation Index (DFI) and the High DNA Stainability (HDS), which is a display of immaturity of chromatin. SCSA is repeatable, and appropriate to the large sample throughput but again functions on the population level- i.e. it is not directly connected to the image of individual sperm. This single-cell granularity does not allow it to be useful in the supervised training pipelines in AI that requires paired image-label data.

Comet assay [8], also referred to as single-cell gel electrophoresis, is a visualization of DNA strand breaks under the influence of an electric field. Damaged DNA leaks out of nucleus creating a corona trail (comet tail) that shows the extent of damage. Even though it gives a direct visual confirmation of the integrity of the DNA, it is a technically challenging, low-throughput and highly operator-technique-dependent method. A more recent variant is the SCD/HALO assay, which is a less sensitive method that uses a halo

formation following chromatin deproteinization and is therefore less expensive, but less sensitive than TUNEL or Comet.

Altogether, these assays have played a significant role in furthering our knowledge of sperm genomic stability, but they have certain limitations in common. They are devastating, laborious, and costly and limit their implementation in massive screening. Further, heterogeneity between protocols and thresholds between assays makes meta-analyses and clinical interpretation complicated. In the case of AI-based studies, these inconsistencies become a major issue when data across multiple centers is to be labelled.

❖ ***AI in Semen Analysis: Progress and Gaps***

The use of artificial intelligence (AI) in semen analysis has experienced an impressive increase, mainly because of the development of digital microscopy, high-resolution imaging, and deep learning. Convolutional Neural Networks (CNNs) and sperm analysis have not been an exception as CNNs have proven to be effective in different medical imaging tasks. Artificial intelligence (AI) has been trained to detect sperm, analyze the motion of the latter, classify the morphology, and predict the vitality. Compared to traditional rule-based image processing, these systems can learn with the data provided and remove the subjective bias as well as enhance precision in their diagnostics [32].

Recent literature has moved the idea of AI to analyze DNA fragmentation based on microscopic images. As an example, VGG16 and ResNet CNNs that have been pretrained on visual features have been trained on visual features correlated with chromatin damage determined using acridine-orange-stained visualization of fluorescence images. The label-free imaging modalities which have been used by other researchers include Quantitative Phase Imaging (QPI) and digital holography, in which the refractive index changes in the sperm head reflect the degree of chromatin condensation. The development of machine learning models, which have been trained on QPI data, has already been able to predict the state of DNA integrity without the use of chemical staining and opened the way to non-destructive real-time assessment of SDF [12].

Although positive outcomes have been achieved, there are a number of bottlenecks. Data scarcity is the main issue, i.e. there is extremely little publicly accessible data, with paired sperm images and SDF ground-truth labels. Hand-labeling of sperm images using SDF yields are tedious, expensive and subject to inter-observer error. Therefore, majority of the studies are based on small datasets, which make generalization and reproducibility of the models difficult.

Domain heterogeneity is another significant weakness. Of the wide variety of imaging conditions in different laboratories-differences in the optics of the microscope, differences in illumination, stain and magnification introduce domain shift that worsens cross-site model performance. Unless domain adaptation [29], [35] or harmonization is relatively strong, AI models which have been trained on a particular dataset fail in another. These issues demand multicenter datasets that are big and upheld by standard procedures and well characterized metadata such as abstinence period, age, and modality of imaging.

❖ ***Data Resources and Imaging Modalities***

The use of modern technologies in the microscopy has made it possible to have repositories of the image of the massive sperm. These are videos of bright-field, phase-contrast, and fluorescence images, and motility videos. Nonetheless, there are few publicly available datasets that are used to conduct research. SCSA or TUNEL slide fluorescent acridine-orange (AO) images offer useful supervision of CNN training because the patterns of AO intensity are associated with DNA fragmentation moderately. Label-free methods of imaging, e.g. QPI or holographic microscopy, encode geometrical features

such as differences in refractive indices, which are correlated to chromatin integrity. This type of modalities provides a viable alternative to be adopted in clinical practice because they do not require chemical stains and maintain cell viability [11].

The bright-field imaging is the most accessible and low-cost modality in the clinical practices, still, it is problematic in terms of DNA fragmentation analysis because explicit molecular contrast is absent. To address this, scientists have suggested multimodal and self-supervised methods of learning, involving the combination of both bright-field and fluorescence domains of information. These hybrid models enable AI models to learn the SDF indirectly based on morphological and textural information that is present in the unstained images [38].

■ **Issues with AI Infertility Diagnostics**

Although these are significant steps taken according to the literature, there are some critical gaps that need to be addressed before the translation of the techniques into the clinics:

1. **Annotation Scarcity:** Co-registered ground truth SDF image data with its corresponding single-cell bright-field or fluorescence image data is not readily available. Without an adequate amount of data, deep learning algorithms cannot reach a fairly robust level of performance for heterogeneous populations.
2. **Annotation error:** Human annotation by experts like embryologists is prone to error. Small differences in understanding can lead to an inconsistent ground truth, which can compromise the reliability of the algorithms.
3. **Domain Shift and Heterogeneity:** The datasets are different across different research groups. This is because of differences in imaging parameters, staining techniques, and optical equipment. Without the application of domain adaptation techniques, the model cannot be generalized [29], [35].
4. **Model Interpretability:** CNNs are performing well, but they are black boxes. The model has to be transparent, providing the clinicians with an explanation of the results so that they can trust the results and satisfy the regulatory requirements.
5. **Clinical Validation:** Unlike many proof-of-concept studies, few systems based on AI have been prospectively validated in a real clinical setting or have demonstrated a relationship between AI-predicted SDF and ART results [31].
6. **Privacy and Governance:** There are strict privacy laws in respect of patient information. It is frequently impossible to centrally pool sperm images. Federated learning provides a way out, since it allows decentralized model training at centers, without the need to transfer raw data, comes with its own engineering problems, and requires harmonized protocols.

■ **Filling the Gaps: To Scaling AI Structures.**

In order to address these issues, the recent literature focuses on the establishment of scalable, interoperable frameworks that would integrate multi-center datasets, common annotation schemes, and privacy-preserving learning solutions. The research conducted on federated learning [13], [28] in medical imaging indicates that distributed model training can preserve an equivalent performance as compared to centralized techniques in addition to protecting the privacy of data. Simultaneously, options of domain adaptation [29], [35] and style transfer have been investigated to reduce the variation of imaging in different centers and to bring the distributions of data closer.

The other area of research that is emerging is explain ability. Gradient-weighted Class Activation Mapping (Grad-CAM [26]) and SHapley Additive exPlanations (SHAP [27]) are visualization tools that enable clinicians to understand which concepts are used in model predictions. These interpretability modules included in AI-based decision support systems help improve clinical acceptance and aid regulatory approval.

The need for standardized, multi-institutional, annotated datasets remains paramount. Establishing harmonized datasets that pair high-quality sperm images with corresponding DNA fragmentation measurements is critical for relatively robust supervised learning. Such datasets would also facilitate meta-learning and transfer learning, enabling generalization across different microscopy platforms.

In the literature, there are a number of themes that arrive at a common point. Although the WHO guidelines and standard procedures of semen analysis have enhanced reproducibility, subjectivity and inter-laboratory variation remains. The DNA fragmentation in sperm presents a potent molecular biomarker with a strong correlation with reproductive outcome which is, however, destructive and resource intensive at present. Artificial intelligence and deep learning is a potential solution to automatically, scale, and optimize SDF prediction using non-destructive imaging data. Nonetheless, this vision relies on the establishment of multi-modal image datasets (including verified DNA fragmentation labels) that are annotated comprehensively.

3. PROPOSED MODEL AND METHODOLOGY

This section presents a scalable, AI-enabled clinical decision support pipeline for infertility diagnosis with a focus on predicting sperm DNA fragmentation (SDF) [3]–[5] alongside conventional semen parameters. The pipeline spans dataset curation, annotation, preprocessing and segmentation, model design, federated training, calibration, evaluation, validation, relatively robustness checks, and a clinician dashboard. Figures and algorithms are labelled for clarity and easy cross-reference.


3.1 Dataset curation and harmonization

Scope. The pipeline ingests bright-field, phase-contrast, fluorescence acridine-orange (AO), and optional label-free quantitative phase imaging [33], [34] (QPI) from clinical partners and public sources.

Steps.

- **Data ingestion:** De-identified raw image and short video Data with site-level metadata stored in a data registry.
- **Metadata harmonization:** Age, abstinence, semen Volume, staining protocol, magnification, numerical Aperture, exposure, camera bit depth, and assay type Descriptions harmonized against WHO 6th Edition [1] and ISO 23162:2021.
- **Quality filtering:** Automated focus and sharpness Analysis, along with human validation of stratified samples for blurred frames, severe overlap, out-of-focus fields, and compression artefacts.
- **Data contracts:** Modality menus, file formats, and Versioned operating procedures defined on a site-by-site Basis. Raw data stored as TIFF with JSON for meta data and checksums for audit.

Figure 1. End-to-end intake and harmonization. A registry coordinates sources, applies QC, and records governance constraints




3.2 Annotation pipeline

Goal: Produce high-quality ground truth for supervised learning and fair benchmarking.

Process:

- **Double-blind labeling:** Two embryologists grade morphology and motility under WHO criteria in a web interface that hides peer labels and enforces label schemas.
- **SDF labels:** For paired datasets, per-cell SDF labels come from TUNEL or AO green/red ratios. Per-sample DFI and HDS come from SCSA. All numeric labels carry units and assay configuration hashes.
- **Agreement and adjudication:** Compute Cohen's κ and percent agreement at session close. Conflicts enter a consensus queue for senior review with structured rationales.
- **Provenance:** Every label includes anonymized annotator ID, timestamp, software version, microscope settings, and image checksum.

Figure 2. Double-blind annotation workflow that reduces subjectivity and captures provenance.




3.3 Preprocessing and segmentation

SpermSegCrop module. Detect, crop, and optionally segment single cells. Link each crop to metadata and assay labels.

- **Detection:** YOLO [25]v5 or YOLO [25]v8 locates heads and tails on full frames. Non-max suppression is tuned for clustered cells.
- **Cropping:** Normalize to 224×224 with padding and physical-scale tags in micrometers per pixel.
- **Segmentation:** Optional U-Net [24] or lightweight UNet++ produces masks for head, midpiece, and tail. Morphometrics are derived from masks.
- **Identity:** Assign a unique CellID that persists across modalities for the same cell using

stage coordinates or registration.

Figure 3. SpermSegCrop preprocessing. Detector-to-crop pipeline with optional semantic masks.



Algorithm 1. SpermSegCrop

Input: Raw image or video frame.

Output: List of standardized single-cell crops.

1. Run YOLO [25]v5 or YOLO [25]v8 to localize candidate sperm cells.
2. For each box, crop and resize or pad to 224×224 . Record physical scale.
3. If enabled, run U-Net [24] to produce head, midpiece, tail masks.
4. Assign CellID and link to metadata and assay records.
5. Persist crops, masks, and lineage to the training store.

3.4 Study design and ground truth

- **Aim:** Predict per-cell and per-sample SDF from microscope images to support objective diagnosis and ART decisions.
- **Design:** Multicenter, prospective imaging study with standardized imaging and SDF assays. One complete site is held out for external validation to measure domain transfer.
- **Cohorts.**
 1. Men undergoing infertility evaluation. Stratify by age, varicocele, smoking, and planned ART.
 2. Exclude active infections and recent gonadotoxic therapies.
 3. Power analysis targets AUROC at or above 0.80 for clinically relevant DFI cut-offs.
- **Ground truth.**
 1. Primary. SCSA for continuous DFI and HDS due to throughput and reproducibility.
 2. Secondary. TUNEL on aliquots from the same sample to enable cross-assay transfer and per-cell labels.
- **Imaging protocol.**
 1. Acquire bright-field and AO fluorescence on the same cells when feasible via micro-registration. Add QPI where available.
 2. Standardize magnification, numerical aperture, exposure, and bit depth across centers.
 3. Store raw TIFF and associated logs with coded IDs.

3.5 Labels and targets


- **Masks.** Weakly supervised masks for head, midpiece, tail with human QA on a stratified subset.

- **Regression targets.** Per-cell AO green/red ratio. Per-sample DFI and HDS from SCSA.
- **Binary targets.** Fragmented vs non-fragmented at assay thresholds evaluated per site.
- **Morphology classes.** Strict Tygerberg categories for multi-task learning.

3.6 Multi-task deep learning

- **Model name:** MultiTaskSpermNet.
- **Backbone:** EfficientNet [23]-B3 or ResNet [22]-50 for 2D images. Optional temporal encoder using a 3D CNN or a small Vision Transformer over frame stacks for motility.
- **Heads:**
 1. **Morphology.** Softmax classification of normal and abnormal subtypes.
 2. **SDF.** Regression of continuous DFI or calibrated binary classification.
 3. **Motility.** Regression of VCL, VSL, and linearity when videos are available.
- **Loss:** Weighted sum of task losses with focal loss for morphology to handle imbalance.

Figure 4. MultiTaskSpermNet architecture with shared encoder and task heads.



Algorithm 2. MultiTaskSpermNet

- **Input:** Single-cell crop with optional temporal frames.
- **Output:** Morphology class, SDF score, motility parameters.
- 1. Extract features with EfficientNet [23]-B3 or ResNet [22]-50.
- 2. If temporal frames exist, encode motion and concatenate embedding's.
- 3. Predict outputs from task heads.
- 4. Compute joint loss


$$L_{total} = \alpha L_{morph} + \beta L_{SDF} + \gamma L_{mot}$$

5. Train with adaptive weighting and focal loss for class imbalance.

3.7 Multiple-instance learning for sample-level DFI

- **Rationale.** Laboratories report DFI at sample level while images are per cell.
- **Approach.** Attention-based multiple-instance learning [30] (MIL) pools per-cell embedding's to estimate sample DFI and HDS. Uncertainty is estimated with Monte Carlo dropout or deep ensembles.

Figure 5. Attention-based MIL for sample-level DFI. Attention weights highlight cells that influence the estimate.




3.8 Domain generalization and self-supervision

- **Domain shift:** Address differences from microscopes, staining, and illumination.
- **Techniques:**
 1. Instance normalization and style randomization during training.
 2. Source-specific batch normalization when sites differ strongly.
 3. DANN adversarial head, CORAL, or MMD to align features [36].
 4. Self-supervised masked image modeling on unlabeled crops to improve relatively robustness and reduce label demand.

3.9 Federated learning and privacy preservation

- **Motivation:** Clinical data cannot be centralized in many regions.
- **Method:** Federated averaging with secure aggregation trains a global model without moving patient data.

Figure 6. Federated training with secure aggregation.



Algorithm 3. Federated Training

- **Input:** Global weights W_0 , local datasets at N clinics.
- **Output:** Updated global model.
 - Broadcast W_t to clients.
 - Each client trains E local epochs to produce W_i .
 - Send encrypted ΔW_i to server.
 - Aggregate

$$W_{t+1} = \sum_i \frac{n_i}{\sum_j n_j} W_i$$

- Repeat until validation performance plateaus.

3.10 Data augmentation and normalization

- **Per-image:** small rotations, mild crops, brightness and contrast jitter, Gaussian noise, light blur, and motion blur, as well as changes in gamma and elastic transformations, all within clinically reasonable bounds.
- **Domain-aware:** random point spread functions, illumination patterns to mimic other centers, mix-up or CutMix for regularization, and label mixing for regularization.
- **Normalization:** image-wise mean and standard deviation, QPI in physical units after instrument calibration.

3.11 Optimization and regularization

- **Optimizer.** AdamW with initial learning rate 1e-4 and cosine decay.
- **Batch size.** 32 per GPU where feasible, 16 on federated clients.
- **Weight decay.** 1e-4.
- **Early stopping.** Monitor SDF AUROC and combined validation loss with patience windows.
- **Regularization.** Dropout 0.3 to 0.5 in heads. Label smoothing 0.1 for morphology.

3.12 Calibration and post-processing

SDF probability calibration.

- Temperature scaling with T chosen to minimize negative log-likelihood on validation.
- Optional isotonic regression for nonparametric calibration.

Metrics. Brier score and Expected Calibration Error.

Sample-level DFI. Aggregate per-cell predictions with mean, median, and trimmed mean. Select the aggregator by validation MAE against SCSA.

3.13 Evaluation strategy

❖ **Per-cell.**

- Morphology: accuracy, precision, recall, F1 per class, macro-F1, Cohen's κ .
- SDF binary: AUROC, AUPRC, sensitivity at 90 percent specificity, confusion matrix.
- SDF continuous: MAE, RMSE, Pearson and Spearman correlation with DFI.
- Calibration: Brier score and ECE, reliability diagrams.

❖ **Per-sample.**

- Compare predicted and laboratory DFI or HDS using Bland–Altman plots, correlation coefficients, regression slope and intercept, and MAE.
- Report strata that matter clinically: less than 15 percent, 15 to 30 percent, greater than 30 percent DFI.

❖ **Clinical endpoints.**

- Exploratory association with fertilization, blastulation, clinical pregnancy, and live birth using logistic models or Cox models with confounder adjustment.

❖ **Statistics.**

- DeLong tests for AUROC comparisons.
- Paired t-test or Wilcoxon signed-rank for MAE differences.
- Benjamini–Hochberg correction when comparing many models.

3.14 Validation protocol and reproducibility

- **Internal.** Patient-wise 5-fold cross-validation without cross-patient leakage. All splits are stratified by site and assay.
- **External.** Entire site held out to test generalization and microscope swap effects.
- **Prospective.** Pre-registered cohort with fixed thresholds and a locked model for forward-only evaluation.
- **Reproducibility.** Release fixed seeds, pre-processing scripts, versioned model cards, and bootstrap confidence intervals.

3.15 Ablation and relatively robustness checks

- Remove task heads to quantify benefits from multi-task transfer.
- Swap backbones: EfficientNet [23] vs. ResNet [22] vs. small ViT.
- Turn off augmentation classes to measure domain sensitivity.
- Compare centralized vs. federated training were permitted by governance.
- Stress tests: JPEG compression, under and over exposure, synthetic blur, down sampling, and sensor noise profiles.

3.16 Clinician-facing dashboard and quality control


Outputs.

- Per-cell saliency maps from Grad-CAM [26] and concept activation vectors aligned with chromatin density features. When AO is present, show side-by-side overlays.
- Uncertainty bands from ensembles or Monte Carlo dropout at cell and sample levels.
- Sample-level summaries that combine WHO parameters, AI-predicted SDF, and confidence flags with concise textual interpretations.
- Auto-generated PDF reports and LIS export with structured fields.

QC.

- Drift detection on slice-level statistics. Alerts trigger when feature distributions leave training bounds. Provide suggested checks and a retry capture protocol.

Figure 7. Clinician dashboard with explanations, uncertainty, and drift checks.



3.17 Notation and objective

Let $X = \{x_i\}$ be single-cell crops or short frame stacks.

Let $y_i^{\text{morph}} \in \{1, \dots, C\}$ be morphology class.

Let y_i^{SDF} be SDF ground truth as continuous DFI in $[0, 100]$ or binary.

Let $y_i^{\text{mot}} \in \mathbb{R}^k$ be motility parameters.

The model $f_{\theta}(x_i)$ outputs $p_i^{\text{morph}}, \hat{y}_i^{\text{SDF}}, \hat{y}_i^{\text{mot}}$.

The Training Objective is

$L_{\text{total}} = \lambda_m L_{\text{morph}} + \lambda_s L_{\text{SDF}} + \lambda_t L_{\text{mot}} + \lambda_{da} L_{\text{DA}}$. Use focal loss for morphology, BCE-with-logits or MSE for SDF, MSE for motility, and an optional domain-adversarial term for invariance. Start with $\lambda_m = \lambda_s = \lambda_t = 1$ and $\lambda_{da} = 0.1$. Consider uncertainty-based weighting during training.

3.18 Training loop

for epoch in 1..N:

for imgs, morph_y, sdf_y, mot_y in train_loader:

imgs = augment(imgs)

morph_logits, sdf_logits, mot_preds, features = model(imgs)

$L_{\text{morph}} = \text{FocalLoss}(\text{morph_logits}, \text{morph_y})$

$L_{\text{sdf}} = \text{BCEWithLogits}(\text{sdf_logits}, \text{sdf_y})$ # or MSE for DFI regression

$L_{\text{mot}} = \text{MSE}(\text{mot_preds}, \text{mot_y})$

$L_{\text{total}} = \lambda_m * L_{\text{morph}} + \lambda_s * L_{\text{sdf}} + \lambda_t * L_{\text{mot}}$

if use_domain_adversarial:

$L_{\text{total}} += \lambda_{da} * \text{DomainLoss}(\text{features}, \text{domain_labels})$

optimizer.zero_grad()


$L_{\text{total}}.\text{backward}()$

optimizer.step()

validate()

update_scheduler()

Figure 8. Training loop summary with augmentation, multi-task loss, optional domain alignment, and validation control.




3.19 Architecture summary

Hybrid encoder-decoder with attention.

1. Transfer encoder: ResNet [22]-50 or ViT-small.
2. U-Net [24] decoder for optional masks and Morphometrics.
3. Adaptive attention module to fuse shape and fluorescence cues when AO is present.
4. Consensus segmentation layer to stabilize masks across sites.
5. Feature fusion that combines morphological and fluorescence descriptors.
6. SDF classifier or regressor to output fragmentation probability or DFI.


Figure 9. Hybrid architecture that joins structure and signal for precise SDF inference.



3.20 Lessons for this work

1. CNNs detect image cues linked to SDF that go beyond manual morphology grading.
2. Morphology and DNA integrity are correlated, which supports the value of multi-task learning.
3. Motility modelling is mature but benefits from integration with molecular markers such as DFI.
4. Dataset heterogeneity is the main barrier to deployment. Domain-aware training and federated learning [13], [28] reduce this risk and improve generalization.

Figure 10. AI-driven Computer Assisted System: A Scalable Framework for Clinical Decision Support System to Infertility Diagnosis



4. PERFORMANCE ANALYSIS AND EXPERIMENTAL RESULTS

The performance of the proposed AI-driven Computer Assisted System was evaluated against several benchmark models using both cell-level and sample-level sperm image datasets. The key objective was to validate the scalability and relatively robustness of the proposed MultiTaskSpermNet model and its federated variant in predicting sperm DNA fragmentation (SDF) [3]–[5] and related morphology parameters.

1. Experimental Setup

- **Dataset composition:** Combined clinical and open-source datasets, totalling over 45,000 annotated sperm images with corresponding DNA fragmentation indices (DFI).
- **Hardware:** Training conducted on distributed GPUs (NVIDIA RTX 6000) with federated nodes simulating three independent clinical sites.
- **Validation:** Five-fold cross-validation, assayed on one external hold-out site to test generalization.
- **Metrics used:**
 - **Accuracy:** Morphology classification accuracy.
 - **AUROC (SDF):** Discriminative ability for predicting DNA fragmentation.
 - **MAE (DFI):** Error between predicted and laboratory DFI values.
 - **Spearman r:** Correlation between predicted and ground-truth DFI.
 - **Cohen's κ :** Agreement between AI and embryologist morphology grades.

2. Comparative Results Summary:

Model	Accuracy	AUROC (SDF)	AUPRC	MAE (DFI)	Spearman r	Cohen's κ
Baseline CNN	0.82	0.78	0.60	6.4	0.72	0.63
ResNet-50	0.87	0.84	0.70	5.2	0.79	0.71
EfficientNet-B3	0.90	0.88	0.75	4.5	0.84	0.76
MultiTaskSpermNet	0.94	0.93	0.86	3.8	0.89	0.83
MultiTaskSpermNet + Federated	0.95	0.94	0.87	3.5	0.91	0.85

The federated multi-task model gave the highest results in all measures indicating higher cross-site generalization and calibration.

Calibration and Confidence

The performance, as well as the probabilities must be reliable to make accurate clinical predictions.

The calibration metrics show that the multi-task federated model results in well-calibrated SDF.

Predictions.

Table 2. Calibration results

Model	ECE (↓)	Brier Score (↓)
Baseline CNN	0.12	0.18
ResNet-50	0.09	0.13
EfficientNet-B3	0.07	0.10
MultiTaskSpermNet	0.04	0.06
MultiTask + Federated	0.03	0.05

- **Bootstrap Confidence Intervals**

The number of bootstrap replicates was 1,000, which was the value used to compute confidence intervals.

Table 3. AUROC bootstrap confidence intervals

Model	Mean AUROC	95% CI Low	95% CI High
Baseline CNN	0.78	0.76	0.80
ResNet-50	0.84	0.82	0.86
EfficientNet-B3	0.88	0.86	0.90
MultiTaskSpermNet	0.93	0.92	0.95
MultiTask + Federated	0.94	0.92	0.96

The narrow confidence intervals confirm model reliability, while the upward shift in AUROC for advanced architectures supports performance gains.

Robustness across Imaging Conditions:

To model clinical variability a certain degree of degradation (blur, low) was used to test the model. (Light, compression, mixed microscopes). There was a high value of the federated model in terms of the AUROC across all conditions.

Table 4. AUROC under imaging degradations

Scenario	EfficientNet-B3	MultiTask	Federated
Reference	0.88	0.93	0.94
Blurred	0.84	0.90	0.91
Low-light	0.85	0.91	0.92
JPEG compression	0.86	0.92	0.93
Mixed microscopes	0.87	0.93	0.93


3. Graphical Results

Figure 1. Model Performance Comparison



The performance of the models in major measures is indicated in the bar chart below. The MultiTaskSpermNet + Federated model achieved better results than all baselines in terms of accuracy, AUROC, correlation, and so forth and k agreement measures, which are more robust and reproducible demonstratively.

Figure 2. Mean Absolute Error (DFI)



A clear decreasing trend in MAE was observed as model complexity and multi-task learning improved. The federated model achieved a 45% reduction in DFI prediction error compared to the baseline CNN.

Figure 3. Calibration Metrics by Model




Figure 4. Simulated ROC Curves for Models





Figure 5. AUROC across Imaging Scenarios



4. Key Observations

1. Accuracy and Robustness:

- The baseline CNN achieved an accuracy of 82%, while the MultiTaskSpermNet reached 94%.
- Federated learning improved model stability across different microscopes and staining methods, increasing generalization by ~3%.

2. SDF Prediction (AUROC and MAE):

- The reviewed framework achieved an AUROC of 0.94, significantly outperforming ResNet [22]-50 (0.84).
- The mean absolute error dropped from 6.4 to 3.5 DFI units, confirming better regression accuracy.

3. Correlation Analysis:

- Spearman's rank correlation increased from 0.72 (Baseline) to 0.91 (Federated MultiTaskSpermNet), indicating high alignment between predicted and actual SDF values.
- Pearson correlation (not shown) mirrored this trend with $r \approx 0.90$.

4. Morphology Agreement:

- Cohen's κ improved from 0.63 to 0.85, suggesting that AI-based grading achieved near-expert agreement levels, reducing inter-operator variability.

5. Cross-Site Validation:

- Performance drop in unseen site testing was only 2–3%, confirming domain relatively robustness.
- Traditional CNNs saw up to 10% performance loss under microscope or staining variations.

6. Additional Robustness Tests

Table 2. Model performance under varied imaging and acquisition conditions.

Test Condition	Accuracy	AUROC (SDF)	Δ from Baseline
Normal lab images (reference)	0.95	0.94	—
Blurred images (5% Gaussian blur)	0.91	0.90	–4%
Low-light conditions	0.92	0.91	–3%
JPEG compressed (85%)	0.93	0.92	–2%
Mixed microscopes (cross-domain)	0.93	0.93	–1%

The system maintained strong performance even under degraded or cross-domain conditions, indicating real-world adaptability.

6. Qualitative Results

- **Grad-CAM [26] visualization:** Highlighted chromatin-dense regions in sperm heads correlated with DNA fragmentation, providing interpretable cues for clinicians.
- **Attention pooling maps:** Displayed high weights on fragmented cells, validating the model’s focus during sample-level DFI prediction.
- **Dashboard analysis:** Presented confidence intervals and flagging of outlier cases for review.

7. Statistical Validation

- DeLong’s test confirmed significant AUROC improvement between baseline CNN and MultiTaskSpermNet ($p < 0.001$).
- MAE differences across models were statistically significant (paired t-test, $p < 0.05$).
- Bootstrap resampling ($n = 1000$) confirmed stable confidence intervals ($\pm 1.5\%$ for accuracy).

The proposed AI-driven system outperformed all baseline and single-task models in accuracy, calibration, and interpretability. Federated training improved cross-lab reproducibility while maintaining data privacy. Multi-task learning leveraging morphology and motility enhanced SDF prediction performance. Robustness tests confirmed reliable performance under variable imaging conditions.

9. Conclusion from Experimental Analysis

The results strongly validate that the proposed MultiTaskSpermNet with Federated Learning provides a scalable, explainable, and privacy-preserving AI solution for infertility diagnostics. It achieved:

- 95% morphology classification accuracy
- 0.94 AUROC for SDF prediction
- 3.5 MAE in DFI regression
- 91% correlation with laboratory ground truth

5. CONCLUSION

This review aims to summarize recent progress in neural network-assisted, non-destructive prediction of sperm DNA fragmentation and its implications within the overall framework of robust and reliable learning systems for medical image processing. The discussion points to an inherent weakness in current approaches to reproductive health diagnostics, as there is currently no standardized large-scale and well-annotated dataset available to jointly describe sperm morphology, motility, and ground truth molecular data. This is an essential step to bring deep learning approaches from the realm of proof-of-concept to robust and reliable decision-making systems.

A common trend across recent works is the application of multi-task learning architectures to enhance robustness and prediction accuracy. The current frameworks utilize joint modeling of morphology classification, estimation of motility, and prediction of SDF, thereby enhancing the overall capabilities of learning representations. The empirical results suggest that multi-task learning architectures can attain high discriminative power in predicting SDF, with high agreement with ground truth data, thereby supporting the claim that morphology and optical features carry latent information regarding DNA integrity.

From a systems perspective, standardized data curation pipelines, harmonized metadata schemes, and double-blind annotation methods are critical in reducing inter-laboratory variations. The integration of federated learning extends this paradigm, allowing for distributed optimization across clinical sites without compromising data privacy. This approach to training models maintains the privacy constraint while continuing to improve global model generalization, thus aligning the field of neural networks with real-world governance constraints in healthcare.

Another significant focus of the review is the need to improve interpretability and calibration in the context of safety-critical clinical deployment. Gradient-based saliency mapping and attention-based pooling are critical in creating a direct link between predictions and biological image regions, thus instilling confidence in clinical decision-making. These mechanisms, in conjunction with a dashboard for clinicians to visualize uncertainty and sample-level summaries, transform a black box model into a transparent clinical decision support system.

Overall, the experimental results demonstrate the viability of deep learning models in identifying subtle visual and optical cues associated with sperm DNA damage, extending beyond the scope of conventional human microscopy. Performance in heterogeneous imaging conditions, including variations in microscope hardware, illumination, and staining, indicate robust cross-domain resilience and scalability to multi-center environments.

Looking forward, the advancement of this field will largely depend on the development of harmonized multi-institutional datasets, domain generalization methods, self-supervised pre-training strategies, and federated optimization methods. As a fusion of advancements in neural network architectures, distributed learning, and explainable learning, non-

destructive SDF prediction appears to be a compelling application domain for the advancement of the next generation of neural networks and learning systems. These advancements not only improve the capabilities of the underlying computational methodologies but also move the field of reproductive medicine towards objective, reproducible, and data-driven precision diagnostics.

❖ **FUTURE SCOPE**

Finally, this study confirms the ability of AI-based systems of the decision support to become a potent addition to the traditional semen analysis, allowing quicker, reproducible, and more objective methods of diagnosing male infertility. This framework enables the implementation of fertility assessment apparatus around the world, using standardized instruments, by concatenating high-quality image data with privacy-preserving learning architecture. It is a highly promising bridge of the gap between laboratory-based molecular assays and real-time non-destructive imaging diagnostics - a step to precision and data-driven reproductive medicine. Although the findings of this paper are promising, there are still a number of avenues through which this can be extended clinical translation and improvement. The directions that follow are a roadmap of the future work.

1. Multi-Modal DataIntegration:

The increase of the biological signals, including genomic, proteomic, and metabolomics information, can enhance the model in terms of understanding the male reproductive health. Multi-modal integration of image based and molecular based data may be used to discover extensive models with the ability to predict not only DNA fragmentation but functional integrity of the sperm as a whole.

2. Improvement in the use of Annotation Tools:

The process of annotating manuals, despite being correct, is labour intensive. The future research must utilize AI-based labelling systems and semi-supervised annotation systems to minimize the work of experts. Active learning has the potential to prioritize uncertain samples or diverse samples to be reviewed by humans, accelerating dataset enlargement and increasing label consistency.

3. Explainability and Regulatory Readiness:

It will also be possible to provide the AI decisions with more clarity by expanding the interpretability layer with quantitative explanation scores (e.g., feature importance indices or feature relevance scores). The creation of standardized interpretability specifications would help in regulatory accreditations of medical equipment authorities to be deployed clinically.

4. Federated Extensions: Federated and Distributed Learning Extensions:

It will also demand a better communication protocol and differential privacy to be able to scale federated learning [13], [28] to dozens of international sites. It is possible to extend federated analytics to meta-learning so that the model of each clinic can be locally adapted and contribute to a global consensus model.

5. Live and Mobile Diagnostics:

Smartphone-linked or portable microscopes with lightweight AI-based inference models have the potential to bring fertility testing outside clinical laboratories, particularly in low-resource areas. On-device versions of the system based on edge inferencing would be able to analyse sperm and remain private.

6. Longitudinal Tracking and Predictive Analytics:

It would be possible to expand the system to monitor the sperm quality trends over time in patients. With temporal data, AI can anticipate fertility recovery due to treatment, exposure, or lifestyle change as it provides proactive fertility monitoring.

The creation of this AI-based Computer Assisted System is a significant advance in integrating the clinical imaging, computational intelligence and collaborative data governance. It has shown that privacy-conscious, intelligent systems can be so high in diagnostic accuracy, cross-domain reasonably robust and explainable in a single platform.

With the development of the field, the integration of AI with bioimaging and reproductive medicine will again transform the diagnosis and personalization of infertility treatment. The infrastructure established through this research, which was a high-quality annotated dataset and a scalable, federated AI system, offers a viable roadmap of the next generation of autonomous and data-driven fertility care systems that are precise, just, and clinically dependable.

6. REFERENCES AND FOOTNOTES

- [1] World Health Organization, WHO Laboratory Manual for the Examination and Processing of Human Semen, 6th ed., Geneva, Switzerland: WHO Press, 2021.
- [2] S. C. Esteves et al., "Clinical relevance of routine semen analysis and controversies surrounding strict criteria," *Asian J. Androl.*, vol. 14, no. 4, pp. 555–563, 2012.
- [3] A. Agarwal et al., "Sperm DNA fragmentation: A new guideline for clinicians," *World J. Mens Health*, vol. 34, no. 3, pp. 153–165, 2016.
- [4] L. Simon et al., "Sperm DNA damage and its impact on fertility," *Hum. Reprod. Update*, vol. 23, no. 4, pp. 414–435, 2017.
- [5] J. Zhao et al., "Sperm DNA fragmentation and IVF/ICSI outcomes: A meta-analysis," *Reprod. Biol. Endocrinol.*, vol. 12, p. 123, 2014.
- [6] Y. Gavrieli et al., "Identification of programmed cell death via TUNEL assay," *J. Cell Biol.*, vol. 119, no. 3, pp. 493–501, 1992.
- [7] D. P. Evenson and R. Wixon, "Clinical aspects of SCSA," *Theriogenology*, vol. 65, no. 5, pp. 979–991, 2006.
- [8] N. P. Singh et al., "A simple technique for quantitation of DNA damage," *Exp. Cell Res.*, vol. 175, no. 1, pp. 184–191, 1988.
- [9] Y. LeCun, Y. Bengio, and G. Hinton, "Deep learning," *Nature*, vol. 521, pp. 436–444, 2015.
- [10] S. G. Goodson et al., "Deep learning-based sperm morphology classifier," *Sci. Rep.*, vol. 7, p. 14955, 2017.
- [11] Y. Rivenson et al., "Deep learning in holographic microscopy," *Light Sci. Appl.*, vol. 8, p. 23, 2019.
- [12] Y. Shur et al., "Machine learning prediction of sperm DNA fragmentation," *Sci. Rep.*, vol. 10, p. 19089, 2020.
- [13] B. McMahan et al., "Communication-efficient learning of deep networks," in *Proc. AISTATS*, 2017.
- [14] E. Gatimel et al., "Sperm morphology reproducibility," *Andrology*, vol. 5, pp. 430–438, 2017.
- [15] M. Coetzee et al., "Sperm morphology and fertilization," *Hum. Reprod. Update*, vol. 4, pp. 73–82, 1998.
- [16] R. J. Aitken and G. N. De Iuliis, "Oxidative stress and sperm DNA damage," *Reproduction*, vol. 141, pp. 1–10, 2010.
- [17] S. Sakkas and J. Alvarez, "Sperm DNA fragmentation mechanisms," *Hum. Reprod. Update*, vol. 16, pp. 512–529, 2010.
- [18] T. Cissen et al., "Sperm DNA fragmentation and miscarriage," *Hum. Reprod. Update*, vol. 22, pp. 23–39, 2016.
- [19] A. Osman et al., "Clinical use of sperm DNA fragmentation," *Fertil. Steril.*, vol. 104, pp. 1119–1130, 2015.
- [20] S. Ribas-Maynou and J. Benet, "Single and double strand sperm DNA damage," *Biol.*

Reprod., vol. 100, pp. 256–268, 2019.

[21] G. Litjens et al., “A survey on deep learning in medical imaging,” *Med. Image Anal.*, vol. 42, pp. 60–88, 2017.

[22] K. He et al., “Deep residual learning for image recognition,” in *Proc. CVPR*, 2016.

[23] M. Tan and Q. Le, “EfficientNet,” in *Proc. ICML*, 2019.

[24] O. Ronneberger et al., “U-Net: Convolutional networks for biomedical segmentation,” in *Proc. MICCAI*, 2015.

[25] J. Redmon et al., “YOLOv3: Real-time object detection,” 2018.

[26] R. R. Selvaraju et al., “Grad-CAM,” in *Proc. ICCV*, 2017.

[27] S. M. Lundberg and S.-I. Lee, “SHAP,” in *Adv. Neural Inf. Process. Syst.*, 2017.

[28] Q. Li et al., “Federated learning in medical imaging,” *Nat. Mach. Intell.*, vol. 2, pp. 305–311, 2020.

[29] W. Ganin et al., “Domain-adversarial training,” *JMLR*, vol. 17, 2016.

[30] M. Ilse et al., “Attention-based multiple instance learning,” in *Proc. ICML*, 2018.

[31] A. Esteva et al., “Dermatologist-level classification,” *Nature*, vol. 542, pp. 115–118, 2017.

[32] E. J. Sheller et al., “Federated learning in medical imaging,” 2019.

[33] Y. Park et al., “Quantitative phase imaging,” *PNAS*, vol. 115, 2018.

[34] Y. Jo et al., “Quantitative phase imaging techniques,” *Nat. Photonics*, vol. 11, pp. 123–129, 2017.

[35] J. Wang and D. Deng, “Deep domain adaptation survey,” *IEEE TPAMI*, vol. 40, 2018.

[36] Z. Sun and K. Saenko, “CORAL domain adaptation,” 2016.

[37] R. Caruana, “Multitask learning,” *Mach. Learn.*, vol. 28, pp. 41–75, 1997.

[38] J. Christiansen et al., “In silico labeling with deep learning,” *Cell*, vol. 173, 2018.

[39] E. Kelly et al., “Bias in AI medical imaging,” *NPJ Digit. Med.*, 2019.

[40] D. Topol, “High-performance medicine,” *Nat. Med.*, vol. 25, 2019.



Pankaj S. Umate is a Ph.D. research scholar in the Department of Computer Science and Engineering at Government Engineering College, Aurangabad. He has over six years of academic and research experience in the field of computer science. He completed his Master of Engineering degree in 2019 and his Bachelor of Engineering degree in 2015, both from Government Engineering College, Aurangabad. His research interests include advanced computing technologies and interdisciplinary applications in intelligent systems.



Dr. Vikul Jagansing Pawar is an accomplished academician, researcher, and administrator in the field of Computer Science and Engineering with more than 18 years of combined academic, research and industry experience. He is currently serving as Head of the Department and Assistant Professor at the Government College of Engineering, Aurangabad. He has completed his Ph.D. in Computer Science and Engineering from Osmania University, Hyderabad, under the QIP program.

Dr. Pawar has strong expertise in Artificial Intelligence, Machine Learning, Data Analytics, Image Processing, Cyber Security, and Software Engineering. He has authored several research papers in reputed journals (SCOPUS/ESCI), published book chapters with Springer, secured multiple patents in healthcare and educational technologies, and written a textbook for engineering students.

- 7. DR. KAILASH D. KHARAT IS AN ASSOCIATE PROFESSOR IN DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING, AURANGABAD, MAHARASHTRA, WITH OVER 16 YEARS OF EXPERIENCE IN TEACHING AND RESEARCH. HE HOLDS A PH.D. IN COMPUTER SCIENCE & ENGINEERING, M.E. (2012) IN COMPUTER SCIENCE AND ENGINEERING FROM GOVERNMENT ENGINEERING COLLEGE, AURANGABAD, AND A B.E. (2009) IN COMPUTER SCIENCE AND ENGINEERING FROM GOVERNMENT COLLEGE OF ENGINEERING, AMRAVATI.**



He has published five patents and more than 20 research papers in reputed international journals also published book chapters with Springer and written a textbook for engineering students. He also serves as a reviewer for several recognized journals. His research interests include Data Mining, Data Science, Big data, Pattern Recognition, Image Processing, and Machine Learning.