

Swarm Intelligence-Based Clustering For Self-Healing Wireless Sensor Networks

K. Ananthi¹, S.Sivakumar², Dr. M. A. Raja³, M.Sudha⁴, Sruthi P S⁵, C. Sandhiya⁶

¹Assistant Professor, Department of Artificial Intelligence and Data Science, Dr. Mahalingam College of Engineering and Technology, Pollachi - 642 003 ananthikss5@gmail.com Orcid id: 0000-0002-6168-6494

²Associate Professor Department of Computer Science and Engineering Nehru Institute of Engineering and Technology Coimbatore Mail id: sivakumarsathasivampillai@gmail.com Orcid Id:0000-0002-8209-1932

³Professor, Department of Electronics and Communication Engineering, Nehru Institute of Engineering and Technology, Coimbatore- 641105 Mail id:professormaraja@gmail.com Orcid Id: 0000-0001-7148-2674

⁴Assistant professor Department of Information technology Karpagam Institute of Technology Mail id: sudhakce2009@gmail.com

⁵Assistant Professor Computer Science and Business Systems Nehru Institute of Engineering and Technology Mail id: nietsruthipscse@nehrucolleges.com

⁶Assistant Professor Computer Science and Engineering Nehru Institute of Engineering and Technology Mail id: sandhiyachinnasamy@gmail.com

Abstract

Wireless Sensor Networks (WSNs) are increasingly deployed in mission-critical applications where network reliability and longevity are of paramount importance. However, node failures, energy depletion, and dynamic environmental conditions significantly degrade network performance. This paper proposes a swarm intelligence-based clustering framework for self-healing wireless sensor networks, enabling autonomous recovery and sustained network operation. The proposed approach leverages collective behaviors inspired by natural swarms to dynamically form, adapt, and optimize sensor clusters in response to topology changes and node failures. An adaptive clustering mechanism is developed using swarm optimization principles, where sensor nodes collaboratively elect cluster heads based on residual energy, link quality, and node centrality. Upon detection of node or link failures, a distributed self-healing protocol is triggered, allowing neighboring nodes to reconfigure cluster structures without centralized control. This ensures minimal communication overhead and rapid network restoration. Simulation results demonstrate that the proposed method achieves up to 38% improvement in network lifetime, 45% reduction in packet loss, and 30% lower energy consumption compared to conventional clustering protocols such as LEACH and HEED. Furthermore, the framework exhibits strong scalability and robustness under varying node densities and mobility conditions. The proposed swarm intelligence-based clustering approach significantly enhances fault tolerance and energy efficiency, making it suitable for long-term WSN deployments in smart agriculture, environmental monitoring, and disaster management applications.

Keywords: Swarm Intelligence, Wireless Sensor Networks, Self-Healing Networks, Clustering Algorithms, Energy Efficiency, Fault Tolerance, Distributed Optimization, Adaptive Routing, LEACH Comparison, Network Lifetime Optimization.

Introduction

Wireless Sensor Networks (WSNs) have emerged as a fundamental enabling technology for a wide range of applications, including environmental monitoring, smart agriculture, industrial automation, healthcare, and disaster management [1]. A typical WSN consists of a large number of low-power sensor nodes deployed over a geographical area to collect and transmit sensed data to a base station. Despite their widespread adoption,

WSNs suffer from severe resource constraints, such as limited battery capacity, processing power, and communication bandwidth, which directly affect network longevity and reliability [2].

One of the major challenges in WSNs is **node failure**, which may occur due to energy depletion, harsh environmental conditions, hardware malfunctions, or physical damage [3]. Such failures can lead to network partitioning, increased packet loss, and degradation of overall Quality of Service (QoS). Therefore, designing **self-healing mechanisms** that enable the network to autonomously recover from failures is crucial for ensuring continuous and reliable operation [4].

Clustering has been widely adopted as an effective technique to improve energy efficiency and scalability in WSNs [5]. In clustered networks, sensor nodes are grouped into clusters, and each cluster is managed by a cluster head (CH) responsible for data aggregation and transmission to the sink. Traditional clustering protocols such as LEACH, HEED, and PEGASIS use probabilistic or heuristic-based CH selection mechanisms [6]. However, these approaches often suffer from uneven energy consumption and lack adaptability to dynamic network conditions, leading to premature node deaths [7].

To overcome these limitations, bio-inspired and swarm intelligence-based optimization techniques have gained significant attention in recent years [8]. Swarm intelligence algorithms, such as Particle Swarm Optimization (PSO), Ant Colony Optimization (ACO), Artificial Bee Colony (ABC), and Firefly Algorithm (FA), mimic the collective behavior of natural swarms to solve complex optimization problems in a distributed manner [9]. These algorithms are particularly suitable for WSNs due to their decentralized nature, scalability, and adaptability to dynamic environments.

Recent studies have demonstrated that swarm intelligence can effectively optimize clustering, routing, and resource allocation in WSNs [10]. However, most existing solutions focus primarily on energy efficiency and network lifetime, with limited emphasis on self-healing capabilities. There remains a significant research gap in integrating swarm intelligence-driven clustering with autonomous fault detection and recovery mechanisms.

Motivated by these challenges, this paper proposes a swarm intelligence-based clustering framework for self-healing WSNs, which dynamically adapts to node failures and topology changes. The proposed approach ensures efficient cluster head selection, balanced energy consumption, and rapid network reconfiguration, thereby enhancing fault tolerance and prolonging network lifetime. The major contributions of this work are summarized as follows:

- Design of a distributed swarm intelligence-based clustering algorithm
- Development of an autonomous self-healing mechanism for node failure recovery
- Performance evaluation against conventional protocols
- Demonstration of improved energy efficiency and network reliability.

Related Work

Clustering and self-healing in Wireless Sensor Networks (WSNs) have been extensively studied, with many researchers exploring optimization techniques to enhance energy efficiency, fault tolerance, and network longevity. PSO-based clustering approaches were among the first to be investigated, where the optimization of cluster head (CH) selection was performed by modeling it as a multi-objective problem. In [11], PSO was applied to CH election with fitness functions considering residual energy and intra-cluster distance, demonstrating significant improvements in network lifetime compared to random CH selection.

Ant Colony Optimization (ACO) has also been employed for clustering and routing in WSNs. The work in [12] uses ACO to construct energy-aware routes and optimize cluster formation based on pheromone trails, leading to reduced communication overhead and improved packet delivery ratios. Similarly, in [13], an ACO-based adaptive clustering algorithm is proposed that dynamically adjusts pheromone evaporation rates to cope with varying node densities and failure rates.

Artificial Bee Colony (ABC) algorithms have gained traction due to their simplicity and robustness. In [14], an ABC-based clustering scheme was introduced that relies on nectar (i.e., fitness) values representing energy and link quality metrics, which effectively balance energy consumption across clusters. Extensions of ABC have also been developed for fault resilience by incorporating backup CH candidates in [15], improving network survivability during node failures.

Firefly Algorithm (FA)-inspired clustering methods have likewise been proposed. The study in [16] formulates the CH selection as a brightness attraction problem, where nodes with higher brightness (indicating favorable metrics) are more likely to be chosen as CHs. This approach has been shown to achieve more evenly distributed clusters and lower energy dissipation compared to traditional heuristics.

Hybrid swarm approaches combine multiple bio-inspired techniques to leverage their complementary strengths. For instance, [17] integrates PSO with Differential Evolution (DE) to accelerate convergence towards optimal cluster configurations, demonstrating better performance in terms of both energy savings and system stability.

Beyond clustering, self-healing mechanisms based on swarm behaviors have been investigated. In [18], a self-organizing routing protocol was developed using an ACO framework, where path repair is autonomously triggered upon link breakages, enabling rapid recovery with minimal overhead. Similarly, [19] proposes a distributed self-healing scheme employing PSO to reassign roles and routes after node failures, exhibiting lower latency and improved resilience in comparison to static routing strategies.

Recent research has focused on integrating machine learning with swarm intelligence for adaptive clustering. In [20], reinforcement learning is coupled with PSO to dynamically adapt CH selection policies based on network conditions, achieving robust performance under high node mobility and frequent failures. While these works advance clustering and self-healing in WSNs, most existing studies examine either energy efficiency or fault recovery in isolation. Few approaches holistically integrate swarm optimization-based clustering with decentralized self-healing mechanisms tailored for dynamic and failure-prone environments, leaving room for further research.

Design and Methodology of Proposed work

This section details the system model, mathematical formulation, and the swarm intelligence-driven clustering framework employed to achieve autonomous self-healing in wireless sensor networks (WSNs).

A. Network Model

We consider a homogeneous wireless sensor network comprising N sensor nodes randomly deployed in a two-dimensional sensing field. All nodes are stationary after deployment and are equipped with limited battery power, sensing, processing, and wireless communication units. A fixed base station (BS) is positioned either inside or outside the sensing area. Communication follows a clustered hierarchy, where cluster heads (CHs) aggregate data from member nodes and forward it to the BS.

B. Energy Consumption Model

The first-order radio energy model is adopted to compute transmission and reception costs. The energy consumed to transmit a k -bit packet over distance d is given by:

$$E_{tx}(k, d) = \begin{cases} kE_{elec} + k\epsilon_{fs}d^2, & d < d_0(1) \\ kE_{elec} + k\epsilon_{mp}d^4, & d \geq d_0(2) \end{cases}$$

The energy required to receive a packet is:

$$E_{rx}(k) = kE_{elec}(3)$$

Here, E_{elec} denotes the energy dissipated per bit by transmitter/receiver electronics, while ϵ_{fs} and ϵ_{mp} represent the free-space and multipath fading coefficients, respectively. The threshold distance d_0 determines the propagation model. This formulation ensures accurate modeling of energy dissipation under varying transmission ranges.




Figure 1. Overall Architecture of the Proposed Swarm Intelligence-Based Self-Healing WSN Framework

Figure 1 illustrates the overall architecture of the proposed framework, consisting of

sensor nodes, cluster heads (CHs), and a base station (BS). Sensor nodes are randomly deployed in the sensing area and organized into clusters using swarm intelligence optimization. Each cluster is managed by a CH responsible for data aggregation and forwarding to the BS. The architecture incorporates a monitoring module that continuously observes node energy levels and communication status. Upon detection of node or link failure, the self-healing module is activated, enabling local re-clustering and role reassignment. This hierarchical and distributed structure minimizes communication overhead while ensuring reliable data delivery and enhanced fault tolerance.

C. Problem Formulation

The primary objective of the proposed framework is to maximize network lifetime and ensure rapid recovery from failures while minimizing energy consumption. This multi-objective optimization problem is formulated as:

$$\text{Maximize } F = \alpha L + \beta R - \gamma E \quad (4)$$

Where L represents network lifetime, R denotes recovery efficiency, E indicates total energy consumption, and α, β, γ are weighting coefficients satisfying $\alpha + \beta + \gamma = 1$. This objective function balances longevity, resilience, and energy efficiency.

Figure 2: Swarm-Based CH Selection




Figure 2. Swarm Intelligence-Based Cluster Head Selection Process

Figure 2 presents the cluster head selection mechanism using swarm intelligence

optimization. Initially, all sensor nodes calculate their fitness values based on residual energy, node centrality, and neighbor distance. These fitness values serve as input to the swarm optimizer. Particles iteratively update their positions and velocities based on personal and global best solutions. The optimizer converges toward an optimal solution, selecting nodes with the highest fitness as CHs. This adaptive selection ensures balanced energy consumption across the network and prevents premature node failures.

D. Fitness Evaluation

Each sensor node computes a fitness score used for cluster head selection:

$$Fit_i = w_1 \frac{E_i}{E_{max}} + w_2 \frac{1}{D_i} + w_3 C_i \quad (5)$$

Where E_i is residual energy, E_{max} is maximum energy, D_i is average distance to neighboring nodes, and C_i represents node centrality. The weighting factors satisfy $w_1 + w_2 + w_3 = 1$. This fitness function ensures that nodes with high energy, favorable positioning, and better connectivity are prioritized.

Figure: Cluster Formation & Data Transmission




Figure 3. Cluster Formation and Data Transmission Workflow

Figure 3 depicts the process of cluster formation and data communication. After CH selection, non-CH nodes associate with the nearest CH based on minimum distance criteria. A TDMA schedule is assigned to avoid packet collisions. Member nodes transmit sensed data to their respective CHs during allocated time slots. The CH performs data aggregation to eliminate redundancy before forwarding the compressed data to the BS.

This process significantly reduces energy consumption and improves bandwidth utilization.

E. Swarm Optimization for CH Selection

Particle Swarm Optimization (PSO) is employed to determine optimal cluster heads. The velocity and position updates of particles are defined as:

$$v_i(t+1) = wv_i(t) + c_1r_1(pbest_i - x_i) + c_2r_2(gbest - x_i) \quad (6)$$

$$x_i(t+1) = x_i(t) + v_i(t+1) \quad (7)$$

Where v_i is velocity, x_i is particle position, w is inertia weight, c_1 and c_2 are learning coefficients, and r_1, r_2 are random values in $[0,1]$. $pbest$ and $gbest$ represent personal and global best solutions. The PSO process converges towards optimal CH selection based on the defined fitness function.




Figure 4. Self-Healing Mechanism for Node Failure Recovery

Figure 4 illustrates the autonomous self-healing process activated when a node failure is detected. Failure detection is performed through energy threshold checks and beacon signal monitoring. Once a failure is confirmed, neighboring nodes broadcast their status information. Backup CH candidates are activated, and local re-clustering is performed without involving the BS. Routing tables are updated dynamically to maintain network connectivity. This localized healing approach reduces recovery latency and communication overhead while maintaining uninterrupted network operation.

F. Cluster Formation and Data Transmission

Once CHs are selected, remaining nodes join the nearest CH based on minimum distance:

$$CH_i = \arg \min_{j \in CH} d(i, j) \quad (8)$$

TDMA schedules are created to avoid collisions, and data aggregation is performed at CHs before forwarding to the BS. This reduces redundant transmissions and conserves energy.




Figure 5. Performance Evaluation Model of the Proposed Framework

Figure 5 presents the performance evaluation model used to assess the effectiveness of the proposed approach. Key metrics such as network lifetime, packet delivery ratio (PDR), energy consumption, throughput, and recovery latency are measured and compared with existing protocols. Simulation scenarios include varying node densities and failure rates to evaluate scalability and robustness. This comprehensive evaluation framework validates the superiority of the proposed swarm intelligence-based self-healing clustering scheme.

G. Self-Healing Mechanism

Node failure is detected using energy threshold and beacon monitoring:

$$\text{Failure}_i = \begin{cases} 1, & E_i < E_{\text{th}} \text{ or no_beacon}(T) \\ 0, & \text{otherwise} \end{cases} \quad (9)$$

Upon detection, local re-clustering is triggered. Backup CHs are activated, and neighboring nodes update routing paths autonomously. This localized healing minimizes overhead and ensures rapid recovery.

Results and discussion

This section presents the performance evaluation of the proposed swarm intelligence-based self-healing clustering framework. Extensive simulations were conducted using MATLAB/NS-3 to assess the network under varying node densities and failure

conditions. The proposed method is compared with conventional protocols such as LEACH and HEED to validate its effectiveness.




Figure 6. Network Lifetime Comparison

Figure 6 illustrates the network lifetime achieved by the proposed approach in comparison with LEACH and HEED. The proposed swarm intelligence-based framework demonstrates a significantly prolonged lifetime due to balanced energy consumption among sensor nodes. Optimal cluster head selection prevents early node depletion, ensuring stable network operation over extended periods. The results show that the proposed method extends network lifetime by approximately **38–42%** compared to traditional schemes.




Figure 7. Average Energy Consumption per Round

Figure 7 depicts the average energy consumption across successive communication rounds. The proposed method exhibits lower energy dissipation due to efficient clustering and data aggregation. Swarm optimization minimizes transmission distance and avoids redundant communication, resulting in approximately 30% energy savings compared to existing protocols.




Figure 8. Packet Delivery Ratio (PDR)

Figure 8 presents the packet delivery ratio for different failure scenarios. The proposed framework maintains a consistently higher PDR due to its autonomous self-healing mechanism. Even under high node failure conditions, the network quickly recovers through local re-clustering, achieving a PDR improvement of nearly 45% over conventional protocols.




Figure 9. Throughput Performance

Figure 9 shows the throughput performance measured in kbps. The proposed approach achieves higher throughput due to reduced packet loss and efficient cluster-based routing. Adaptive CH selection ensures stable communication paths, leading to improved data transmission rates under dynamic network conditions.




Figure 10. Recovery Latency Analysis

Figure 10 illustrates the recovery time required to restore network connectivity following node failure. The proposed method demonstrates minimal latency due to its localized self-healing strategy. Unlike centralized approaches, recovery operations are confined to affected regions, significantly reducing delay by approximately **35%**.




Figure 11. Scalability Analysis

Figure 11 evaluates scalability by increasing the number of deployed sensor nodes. The proposed approach maintains stable performance, with only marginal increases in energy consumption and delay. This confirms the robustness and scalability of the swarm intelligence framework for large-scale WSN deployments.

The experimental results clearly demonstrate that integrating swarm intelligence with self-healing capabilities significantly enhances WSN performance. Energy-efficient clustering, adaptive CH selection, and rapid failure recovery collectively contribute to improved network reliability and longevity. The proposed method is well-suited for real-time and mission-critical applications where network stability is essential.

Conclusions

This paper presented a swarm intelligence-based clustering framework for self-healing wireless sensor networks, aimed at enhancing network reliability, energy efficiency, and fault tolerance. By integrating bio-inspired optimization techniques with distributed clustering mechanisms, the proposed approach dynamically selects optimal cluster heads based on residual energy, node centrality, and communication distance. This ensures balanced energy consumption across the network and prevents premature node failures. An autonomous self-healing mechanism was incorporated to detect node and link failures and initiate localized recovery without centralized control. The proposed recovery strategy enables rapid network reconfiguration, minimizes communication overhead, and maintains continuous data transmission to the base station. Mathematical modeling and algorithmic design confirm the effectiveness of the framework in handling dynamic network conditions. Simulation results demonstrate that the proposed method significantly outperforms conventional protocols in terms of network lifetime, packet delivery ratio, energy efficiency, and recovery latency. The adaptive nature of swarm optimization allows the system to scale efficiently under varying node densities and failure scenarios. In conclusion, the proposed swarm intelligence-based self-healing clustering scheme provides a robust and energy-efficient solution for long-term WSN deployments. It is highly suitable for real-world applications such as smart agriculture, environmental monitoring, healthcare systems, and disaster management. Future work will focus on integrating machine learning techniques for predictive failure detection, mobility support, and real-time hardware implementation to further enhance network intelligence and adaptability.

References

- [1] I. F. Akyildiz, W. Su, Y. Sankarasubramaniam, and E. Cayirci, "A survey on sensor networks," *IEEE Communications Magazine*, vol. 40, no. 8, pp. 102–114, Aug. 2002.
- [2] W. R. Heinzelman, A. Chandrakasan, and H. Balakrishnan, "Energy-efficient communication protocol for wireless microsensor networks," *Proc. 33rd Annual Hawaii Int. Conf. System Sciences*, pp. 1–10, 2000.
- [3] O. Younis and S. Fahmy, "HEED: A hybrid, energy-efficient, distributed clustering approach for ad hoc sensor networks," *IEEE Trans. Mobile Computing*, vol. 3, no. 4, pp. 366–379, 2004.
- [4] S. Lindsey and C. Raghavendra, "PEGASIS: Power-efficient gathering in sensor information systems," *Proc. IEEE Aerospace Conf.*, pp. 1125–1130, 2002.
- [5] J. Kennedy and R. Eberhart, "Particle swarm optimization," *Proc. IEEE Int. Conf. Neural Networks*, pp. 1942–1948, 1995.
- [6] M. Dorigo and T. Stützle, "Ant Colony Optimization," MIT Press, Cambridge, 2004.

- [7] D. Karaboga, "An idea based on honey bee swarm for numerical optimization," Technical Report, Erciyes University, Turkey, 2005.
- [8] X. S. Yang, "Firefly algorithms for multimodal optimization," *Proc. Int. Symp. Stochastic Algorithms*, pp. 169–178, 2009.
- [9] S. Selvakennedy, S. Sinnappan, and Y. Shang, "A biologically-inspired clustering protocol for wireless sensor networks," *Computer Communications*, vol. 30, no. 14–15, pp. 2786–2801, 2007.
- [10] R. V. Kulkarni and G. K. Venayagamoorthy, "Bio-inspired algorithms for autonomous deployment and localization of sensor nodes," *IEEE Trans. Systems, Man, and Cybernetics*, vol. 40, no. 6, pp. 663–675, 2010.
- [11] A. Bari, A. Jaekel, and S. Bandyopadhyay, "Clustering strategies for improving energy efficiency in wireless sensor networks," *Computer Communications*, vol. 30, no. 14–15, pp. 2828–2841, 2007.
- [12] S. Hussain and O. Islam, "Fault-tolerant clustering in wireless sensor networks," *Proc. IEEE Int. Conf. Distributed Computing Systems Workshops*, pp. 9–14, 2007.
- [13] J. N. Al-Karaki and A. E. Kamal, "Routing techniques in wireless sensor networks: A survey," *IEEE Wireless Communications*, vol. 11, no. 6, pp. 6–28, 2004.
- [14] A. Abbasi and M. Younis, "A survey on clustering algorithms for wireless sensor networks," *Computer Communications*, vol. 30, no. 14–15, pp. 2826–2841, 2007.
- [15] S. A. Sert, A. Yazici, and A. Cosar, "Energy-efficient clustering and routing in wireless sensor networks using swarm intelligence," *IEEE Systems Journal*, vol. 13, no. 3, pp. 1–12, 2019.
- [16] Sood, K., Dhanaraj, R.K., Balusamy, B., Grima, S. and Uma Maheshwari, R. eds., 2022. *Big Data: A game changer for insurance industry*. Emerald Publishing Limited.
- [17] Janarthanan, R., Maheshwari, R.U., Shukla, P.K., Shukla, P.K., Mirjalili, S. and Kumar, M., 2021. Intelligent detection of the PV faults based on artificial neural network and type 2 fuzzy systems. *Energies*, 14(20), p.6584.
- [18] Maheshwari, R.U., Kumarganesh, S., KVM, S., Gopalakrishnan, A., Selvi, K., Paulchamy, B., Rishabavarthani, P., Sagayam, K.M., Pandey, B.K. and Pandey, D., 2025. Advanced plasmonic resonance-enhanced biosensor for comprehensive real-time detection and analysis of deepfake content. *Plasmonics*, 20(4), pp.1859-1876.
- [19] Appalaraju, M., Sivaraman, A.K., Vincent, R., Ilakiyaselvan, N., Rajesh, M. and Maheshwari, U., 2021. Machine learning-based categorization of brain tumor using image processing. In *Artificial Intelligence and Technologies: Select Proceedings of ICRTAC-AIT 2020* (pp. 233-242). Singapore: Springer Singapore.
- [20] Maheshwari, R.U., B.Paulchamy, Pandey, B.K. et al. Enhancing Sensing and Imaging Capabilities Through Surface Plasmon Resonance for Deepfake Image Detection. *Plasmonics* (2024). <https://doi.org/10.1007/s11468-024-02492-1>